DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Platforma cantarire ET



Producator: Dini Argeo- Italia Capacitate: 300kg, 600kg, 1.500kg, 3.000kg, 6.000kg, 10.000Kg Omologare: Disponibila in variante omologate si neomologate Dimensiune: 100x100cm, 125x125cm, 125x150cm, 150x150cm, 150x200cm, 200x250cm Material platan: Metal vopsit Celule sarcina: 4 celule

Descriere

- Fitted with 4 STAINLESS STEEL shear-beam approved load cells each with 350 Ohm input resistance and made according to OIML R60 standards with protection against dust and under water immersion according to IP68 standards.
- Steel tubular bearing structure, oven-fire painted in RAL 5007 blue; removable loading surface made in extra thick chequered galvanised steel; inspectionable trapdoor housing the junction box.
- Adjustable, stainless steel shock-proof jointed feet and level. Up to 15 Vdc power supply.
- Junction box and wiring cables with sheathing according to IP67 standards, and shielded 5m long 6-pin cable for connection to the indicator complete with connectors.
- Connection to the indicator and calibration with CE-M 3000e single range or 3000e+3000e dual range approval.
- Stainless steel surface.
- High resolution models for internal factory use.
- CCATEX: ATEX certificate for each load cell.
- JB4QA: ATEX certified junction box.
- DCATEXMECH: Declaration of conformity of the whole system composed of PLATFORM + JUNCTION BOX + LOAD CELLS (only if the platform is ordered without the weight indicator; otherwise, refer to the certifications available for the indicator to which it will be connected). WARNINGWith ATEX weighing systems, when directly weighing light metals (such as aluminum, magnesium, titanium and their alloys), it is necessary to use the STAINLESS STEEL loading surface.

Available versions (Versiuni Disponibile)

Code	l x w x h (mm)	Nr. of cells	Max (kg)	d (g)	CE-M* 3000e (g)	CE-M* 2x3000e (g)	d* HR (g)
ETA3	1000x1000x90	4x300kg	300	50	100	--	20
ETA6	1000x1000x90	4x500kg	600	100	200	100-200	50
ETA15	1000x1000x90	4x1000kg	1500	200	500	200-500	100
ETM3	1000x1250x90	4x300kg	300	50	100	--	20
ETM6	1000x1250x90	4x500kg	600	100	200	100-200	50
ETM15	1000x1250x90	4x1000kg	1500	200	500	200-500	100

ETB3	1250x1250x90	4x500kg	300	50	100	--	20
ETB6	1250x1250x90	4x500kg	600	100	200	100-200	50
ETB15	1250x1250x90	4x1000kg	1500	200	500	200-500	100
ETD6	1250x1500x115	4x500kg	600	100	200	100-200	50
ETD15	1250x1500x115	4x1000kg	1500	200	500	200-500	100
ETD30	1250x1500x115	4x2000kg	3000	500	1000	500-1000	200
ETE6	1500x1500x115	4x500kg	600	100	200	100-200	50
ETE15	1500x1500x115	4x1000kg	1500	200	500	200-500	100
ETE30	1500x1500x115	4x2000kg	3000	500	1000	500-1000	200
ETF6	1500x2000x130	4x500kg	600	100	200	100-200	50
ETF15	1500x2000x130	4x1000kg	1500	200	500	200-500	100
ETF30	1500x2000x130	4x2000kg	3000	500	1000	500-1000	200
ETG60	1500x2000x150	4x3000kg	6000	1000	2000	1000-2000	500
ETH30	1500x2500x180	4x3000kg	3000	500	1000	--	200
ETH60	1500x2500x180	4x3000kg	6000	1000	2000	1000-2000	500
ETH100	1500x2500x180	4x5000kg	10000	2000	5000	2000-5000	1000
ETL30	2000x2500x180	4x3000kg	3000	500	1000	--	200
ETL60	2000x2500x180	4x3000kg	6000	1000	2000	1000-2000	500
ETL100	2000x2500x180	4x5000kg	10000	2000	5000	2000-5000	1000

(*) These divisions are obtainable only with the relative options

Caracteristici principale:

- Dotata cu 4 celule de cantarire din otel inoxidabil omologate fiecare cu 350Ohm rezistenta de intrare, sunt facute conform standardelor OIML R60 cu protectie impotriva prafului si imersia apei, avand protectie IP68;
- Structura din otel, tubulara, metal vopsit in RAL 5007 albastru, suprafata de incarcare este demontabila si are in plus fata de Platforma FL, mai multe carouri din otel galvanizat;
- Ajustabila, picioare reglabile si la nivel;
- Pana la 15Vdc sursa de alimentare;
- Cutia de jonctiune si cablurile de alimentare au un invelis in conformitate cu standardul IP67, avand un cablu lung de 5m cu 6 pini pentru conectarea la indicator.
- Optiuni disponibile la momentul comenzii:
  - Conectare la indicator si calibrare cu CE-M 3000e ;
  - Suprafata din otel inoxidabil;
  - Modele de inalta rezolutie pentru uz intern.