DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Platforma cantarire ES



Producator: Dini Argeo- Italia Capacitate: 150kg, 300Kg Omologare: Disponibila in variante omologate si neomologate Dimensiune: 60x60cm Material platan: Metal vopsit Celule sarcina: 4 celule

Descriere

- Fitted with 4 bending beam, stainless steel, approved load cells with IP68 protection from dust and water.
- Very sturdy monobloc steel tubular structure with fixed sheet-steel chequered loading surface.
- IP68 junction box.
- Oven-fire painted RAL 5007 blue.
- Adjustable, antislip feet and level.
- Up to 15 Vdc power supply.
- Shielded 5m long 6-pin cable with connectors for connection to the indicator.
- Connection to the indicator and calibration with CE-M 3000e single range or 3000e+3000e dual range approval.
- Models with special sizes and capacities (ask for estimate).
- Indicator support stand.
- Pit frame for flush floor installation.

Caracteristici principale:

- Dotata cu 4 celule de cantarire din otel inoxidabil cu protectie impotriva prafului si imersia apei, avand protectie IP68;
- Robusta, din otel monobloc cu suprafata de incarcare fixa;
- Cutie de jonctiune;
- Metal vopsit in RAL 5007 albastru;
- Picioare antialunecare, reglabile;
- Pana la 15 Vdc sursa de alimentare;
- Cablu lung de 5m cu 6 pini pentru conectarea la indicator.
- Optiuni disponibile la momentul comenzii:

o Conectarea la indicator si calibrare cu CE –M 3000e, o singura calibrare sau 3000e+3000e la a doua calibrare (in functie de indicatorii utilizati);

Modele cu dimensiuni speciale si capacitati (cereti estimare).