DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Platforma cantarire BFB



Producator: Kern & Sohn - Germania Capacitate: 600kg, 1.500kg, 3.000Kg Omologare: Disponibil in variante neomologate Dimensiune: 100x100cm, 150x125cm Material platan: Metal vopsit Celule sarcina: 4 celule

Descriere

- Weighing bridge with non-slip steel chequer plate, lacquered, overall height 80 mm
- Load cell steel, silicone-coated, IP67 protection
- Display device: KERN KFB-TM, also available separately
- Easy access to the junction box from the top
- Comfortable adjustment of the weighing bridge from above
- Benchtop stand incl. wall mount for display device as standard
- Dynamic weighing: at the push of a button, a stable average weight is given when the environmental conditions are unstable or when weighing animals
- Totalising of weights
- Weighing with tolerance range (checkweighing): Input of an upper/lower limit value. A visual and audible signal assists with portion division, dispensing or grading

For verified scales the weighing bridge must be fixed to the floor. Optionally, with an access ramp, a footplate pair or a pit frame

Limited range of tare with verifiable models (1/6 from [Max])

Shipment via freight forwarder. Please ask for dimensions, gross weight, shipping costs

Available version (Versiuni disponibile)

		g	Verification value [e] g	Minimum load [Min] g		
BFB 600K200SM	600	200	200	4000	1	1
BFB 600K200M	600	200	200	4000	1	1
BFB 1.5T0.5SM	1500	500	500	10000	1	1
BFB 1.5T0.5M	1500	500	500	10000	1	1
BFB 3T1M	3000	1000	1000	20000	1	1
BFB 3T1LM	3000	1000	1000	20000	1	1
BFB 6T-3M	6000	2000	2000	40000		1

Caracteristici principale:

- Pod de cantarire cu anti-alunecare, placa de otel Checker, lacuita, inaltime totala 80 mm;
- Celule de cantarire din otel, acoperite cu silicon, protectie IP67;
- Dispozitivul de afisare KERN KFB-TM este disponibil separat;
- Acces facil la cutia de jonctiune in partea de sus;
- Reglare usoara a podului de cantarire;
- Cantarire dinamica, la o simpla apasare a unui buton;
- Totalizare de greutati;
- Pentru verificarea cantaririlor, podul de cantarire trebuie sa fie fixat la podea.