DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Platforma cantarire FLP



Producator: Dini Argeo- Italia Capacitate: 3.000Kg Omologare: Disponibila in variante omologate Dimensiune: 100x125cm, 125x150 cm Material platan: Metal vopsit Celule sarcina: 4 celule

Descriere

- Fitted with 4 shear-beam 350Ohm nickel-plated steel load cells, approved according to OIML R60 C3 standards (3000 divisions), IP67 protection degree.
- Chequered steel structure and load surface, oven-fire painted, RAL 5007 blue.
- Adjustable, anti-shock jointed feet and level.
- Power supply from 5 to 15 Vdc.
- Hermetic junction box, IP67 wiring with shielded 5m long cable for connection to the indicator.
- Fitted with sideboards and double on/off ramps.
- Upon request: - platform calibration service with weight indicator; - 3000e CE-M approval, to be combined always to the calibration service; - support column for indicator.
- Dimensions in mm of the loading surface: H: height of the loading surfaceH2: total height

Caracteristici principale:

- Dotata cu 4 celule de cantarire din otel, placate cu nichel, aprobata in conformitate cu standardele OIML R60 C3 (3000), grad de protectie IP67;
- Metal vopsit in RAL 5007 albastru;
- Anti soc, picioare articulate reglabile si de nivel;
- Sursa de alimentare 5-15 Vdc;
- Cutie de jonctiune ermetica;
- Cablu lung de 5m pentru coenctarea la indicator;
- Echipata cu rampa;
- La cerere:

o Servicii de calibrare platforma cu indicator de greutate;

o Omologare CE 3000e-M, care urmeaza sa fie combinata la serviciul de calibrare;

o Coloana de sprijin pentru indicator.