DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Platforma cantarire LP



Producator: Dini Argeo- Italia Capacitate: 600kg, 1.500Kg Omologare: Disponibila in variante omologate Dimensiune: 100x125cm, 125x150cm Material platan: Metal vopsit sau inox Celule sarcina: 4 celule

Descriere

- Fitted with 4 shear-beam OIML approved load cells each with 350 Ohm input resistance with protection against dust
- Moulded sheet-steel structure and loading surface, oven-fire painted RAL 5007 blue.
- Adjustable, shock-proof jointed feet and level.
- 5/15 Vdc power supply.
- Hermetic junction box, IP67 wiring with screened 5m long 6-pin cable with connectors for connection to the indicator.
- Fitted with one on/off ramp.
- THE STAINLESS STEEL MODEL HAS THE STRUCTURE AND MECHANICS IN AISI304, AND IP68 STAINLESS STEEL LOAD CELLS
- Connection to the indicator and calibration with CE-M 3000e single range or 3000e+3000e dual range approval (depending on the indicators used).
- High resolution model for internal factory use.
- CCATEX: ATEX certificate for each load cell.
- JB4QA: ATEX certified junction box.
- DCATEXMECH: Declaration of conformity of the whole system composed of PLATFORM + JUNCTION BOX + LOAD CELLS (only if the platform is ordered without the weight indicator; otherwise, refer to the certifications available for the indicator to which it will be connected).

CARACTERISTICI PRINCIPALE

- Echipat cu 4 celule de torsiune shear-beam OIML,

- Rezistenta la intrare celule cantarire - 350 Ohmi fiecare

- Protectie împotriva prafului

- Structura din tabla si otel turnat .

-Vopsit in culoarea RAL 5007 albastru

- Picioare articulate reglabile la nivel.

- Cutie de jonctiune inchisa ermetic, cabluri ecranate lungime standard 5m ,IP67 cu 6 pini cu conectori pentru conectarea la indicator.

- Echipata cu o rampa urcare-coborare

- Disponibila si in varianta din inox, IP 68

- Disponibila in varianta omologata si neomologata metrologic.

- Precizie marita pentru varianta neomologata

OPȚIUNI DISPONIBILE LA MOMENTUL COMENZII:

Conectarea la indicator și calibrare cu 3000 diviziuni CE-M sau dubla scala 3000e + 3000e CE-M in functie de

indicatorul utilizat/ales.

OPȚIUNI PENTRU VERSIONEA ATEX

CCATEX: certificat ATEX pentru fiecare celulă de sarcină.

JB4QA: ATEX certificat cutie de joncțiune.

DCATEXMECH: Declarație de conformitate a întregului sistem compus din PLATFORMĂ + JUNCTION BOX + CELULE DE SARCINĂ (numai dacă platforma este comandată fără indicator; altfel, vezi certificatele disponibile pentru indicatorul la care va fi conectată).