**DATA SPEED S.R.L.**
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

# Platforma cantarire PB




Producator: Dini Argeo - Italia Capacitate: 6kg, 15kg, 30kg, 60kg, 150kg, 300kg, 600Kg Omologare: Disponibila in variante neomologate si omologate Dimensiune: 300x300mm, 400x400mm, 600x600mm, 800x800mm Material platan: Inox Celule sarcina: O celula

## Descriere

- Functioning with a “single point” 350 Ohm aluminium load cell, approved according to OIML R60 C3 standards (3000 divisions), IP65 protection degree.
- Steel tubular structure, oven-fire painted blue, with adjustable resting feet and level.
- Fitted with stainless steel loading surface.
- Up to 15 Vdc power supply.
- Shielded cable for connection to the indicator.
- Upon request: - 3000e CE-M approval; - support column for indicator.

Weighing platform: Available versions

| Code | l x w x h (mm) | Max (kg) | d (g) | CE-M* 3000e (g) |
|---|---|---|---|---|
| PBT6 | 300x300x130 | 6 | 2 | 2 |
| PBT15 | 300x300x130 | 15 | 5 | 5 |
| PBT30 | 300x300x130 | 30 | 10 | 10 |
| PBQ30 | 400x400x140 | 30 | 10 | 10 |
| PBQ60 | 400x400x140 | 60 | 20 | 20 |
| PBQ150 | 400x400x140 | 150 | 50 | 50 |
| PBX60 | 600x600x150 | 60 | 20 | 20 |
| PBX150 | 600x600x150 | 150 | 50 | 50 |
| PBX300 | 600x600x150 | 300 | 100 | 100 |
| PBE300 | 800x800x165 | 300 | 100 | 100 |
| PBE600 | 800x800x165 | 600 | 200 | 200 |

(*) CE-M divisions are obtainable only with the relative options.

| Code | Description |
|---|---|
| DINICAL1 | Calibration service for platform up to 30 kg, connected to Dini Argeo weight indicator - NET PRICE |
| DINICAL2 | Calibration service for platform from 31 to 1500 kg, connected to Dini Argeo weight indicator - NET PRICE |

Legal for trade approval , class III or IIII, with Dini Argeo indicator (only at time of order)

Attached columns

Floor columns

Calibration service (ACCREDIA/DAKKS) only at time of order

CARACTERISTICI TEHNICE

Funcționează cu un "punct unic" 350 Ohm celulă de sarcină din aluminiu, aprobat în conformitate cu standardele OIML R60 C3 (3000 diviziuni), IP65 Grad de protecție.

Structură tubulară din oțel, cuptor la foc vopsit albastru, cu picioarele reglabile și nivelat.

Dotate cu suprafață de încărcare din oțel inoxidabil.

Pana la 15 Vdc alimentare.

Cablu ecranat pentru conectarea la indicator.

La cerere:

- Omologarea 3000e CE-m;
- Coloana suport pentru indicator.