DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Platforma cantarire PBI inox



Producator: Dini Argeo - Italia Capacitate: 6kg, 15kg, 30kg, 60kg, 150kg, 300Kg Omologare: Disponibila in variante neomologate si omologate Dimensiune: 300x300mm, 330x330mm, 400x400mm, 600x600mm Material platan: Inox Celule sarcina: O celula

Descriere

- Functions with a “single point” 350 Ohm aluminium load cell, in stainless steel hermetic cover, approved according to OIML R60 C3 standards (3000 divisions), IP65 protection degree.
- Stainless steel tubular structure, with adjustable resting feet and level.
- Fitted with stainless steel loading surface.
- Up to 15 Vdc power supply.
- Shielded cable for connection to the indicator.
- Upon request: - platform calibration service with weight indicator; - 3000e CE-M approval, to be combined always to the calibration service; - support column for indicator.

Weighing platform: Available versions

Code	l x w x h (mm)	Max (kg)	d (g)	CE-M* 3000e (g)
PBTI6	300x300x130	6	2	2
PBTI15	300x300x130	15	5	5
PBTI30	300x300x130	30	10	10
PBQI30	400x400x140	30	10	10
PBQI60	400x400x140	60	20	20
PBQI150	400x400x140	150	50	50
PBXI60	600x600x150	60	20	20
PBXI150	600x600x150	150	50	50
PBXI300	600x600x150	300	100	100

(*) CE-M divisions are obtainable only with the relative options.

Code	Description
DINICAL1	Calibration service for platform up to 30 kg, connected to Dini Argeo weight indicator - NET PRICE
DINICAL2	Calibration service for platform from 31 to 1500 kg, connected to Dini Argeo weight indicator - NET PRICE

Legal for trade approval , class III or IIII, with Dini Argeo indicator (only at time of order)

Attached columns

Floor columns

Calibration service with Dini Argeo indicator (only at time of order)

CARACTERISTICI TEHNICE

Funcții cu un "punct unic" 350 OHm celulă de sarcină din aluminiu, în capac inox ermetic, aprobat în conformitate cu standardele OIML R60 C3 (3000 diviziuni), IP65 Grad de protecție.

Structură din oțel inoxidabil tubular, cu picioarele de odihnă reglabile și nivelat.

Echipat cu suprafață de încărcare din oțel inoxidabil.

Până la 15 Vdc sursa de alimentare.

Cablu ecranat pentru conectarea la indicator.

La cerere:

- Serviciu de calibrare platformă cu indicator de greutate;
- Omologare 3000e CE-M, care urmează să fie combinate mereu la serviciul de calibrare;
- Coloana suport pentru indicator.