DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Platforma cantarire WALL-E Inox



Producator: Dini Argeo - Italia Capacitate: 6kg, 15kg, 30kg, 60kg, 150kg, 300Kg Omologare: Disponibila in variante neomologate si omologate Dimensiune: 300x300mm, 400x400mm, 600x600mm Material indicator/platan: Inox/Inox Celule sarcina: O celula

Descriere

- Weight indicator with waterproof IP65 STAINLESS STEEL case. Backlit 25mm LCD display with 6 high contrast digits and icons for indication of active functions. Waterproof 5-key functional keypad.
- Functions with an aluminium load cell, protected in IP65 stainless steel cover, approved according to OIML R60 C3 standards (3000 divisions).
- Stainless steel structure, with adjustable resting feet and level.
- Stainless steel loading surface, size: see the table.
- Support column, height: - 350 mm in the "T" models; - 500 mm in the "Q" models; - 700 mm in the "X" models.
- Digital calibration and set-up from keypad or from PC with DINITOOLS.
- Power supply: 230 Vac power supplier.
- X 10 high resolution visualisation
- Net/Gross or lb/kg conversion
- Weighs totalisation
- Formulation
- Counting
- +/- Check
- Percentage weighing
- Alibi (with optional interface)
- HOLD (freezing the weight on the display)
- KEYBOARD: Zeroing, Automatic tare, Presettable tare, printing and/or data transmission, selectable function command, on/off switching.
- PRINTING: Configurable print layout with: - 4 heading lines - Gross-Tare-Net and ticket number - Date and time (only with DFCLK) - Print of barcode 39.

PB platforms: capacities and dimensions

Code	l x w x h (mm)	Max (kg)	d (g)	CE-M* 3000e (g)
WETI6-1	300x300x130	6	2	2
WETI15-1	300x300x130	15	5	5
WETI30-1	300x300x130	30	10	10
WEQI30-1	400x400x140	30	10	10
WEQI60-1	400x400x140	60	20	20
WEQI150-1	400x400x140	150	50	50
WEXI60-1	600x600x150	60	20	20
WEXI150-1	600x600x150	150	50	50
WEXI300-1	600x600x150	300	100	100

(*) These divisions are obtainable only with the relative options

Legal for trade approval

Storing the weighs (only at time of order)

Date&Time option

Communication Interfaces

Connection cables

Remote control

Columns, supports brackets, visors

Code	Description
PBISTF	Fixing bracket for mounting the DFWLI series indicator attached to the PB and PBI series platforms.

CARACTERISTICI TEHNICE

Indicator Greutate cu carcasa de otel impermeabil ,IP65 inoxidabil. Afisaj Backlit LCD de 25 mm cu 6 cifre de contrast înalt și icoane pentru indicarea funcțiilor active. Rezistent la apă, tastatura functionala cu 5 chei.

Funcții cu o celulă de sarcină de aluminiu, protejate în IP65 capac inox, aprobat în conformitate cu standardele OIML R60 C3 (3000 diviziuni).

Structură din oțel inoxidabil, cu picioare reglabile și nivelat.

Suprafață de încărcare din oțel inoxidabil, dimensiune: a se vedea tabelul.

Coloană de sprijin, înălțime:

- 350 mm în modelele "T";
- 500 mm în modelele "Q";
- 700 mm în modelele "X".

Calibrare digitală și set-up de la tastatură sau de la PC prin DINITOOLS.

Alimentare: 230 Vac furnizor de energie.

FUNCȚII SELECTABILE

X 10 vizualizare de înaltă rezoluție

Conversie Net / brut sau lb / kg

Cântărește cu totalizare

Formulare

Socoteală

+/- Verificați

Procentaj de cântărire

Alibi (cu interfață opțională)

HOLD (înghețarea greutatea pe afișaj)

Functii de tastatura și tipografice

Tastatura: tipărire și / sau transmitere a datelor, funcție selectată, pornire / oprire comutare.

Imprimanta: aspect de imprimare configurabil cu:

- 4 linii rubrica
- Gross-proprie-Net și numărul biletului
- Data și ora (numai cu DFCLK)
- Imprimare de cod de bare 39.