DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Platforma cantarire T



Producator: Dini Argeo - Italia Capacitate: 3kg - 600Kg Omologare: Disponibila in variante omologate si neomologate Dimensiune: 230x330mm - 700x700mm Material platan: Inox Celule sarcina: O celula

Descriere

- Functions with an approved aluminium “single point” load cell according to OIML R60 standards with protection against dust and water splashes according to IP65 standards (350 Ohm input resistance).
- Steel tubular structure, oven-fire painted blue, with adjustable resting feet and level.
- Fitted with satined AISI 304 stainless steel loading surface.
- Up to 15 Vdc power supply.
- Shielded 3m connection cable with connectors for connection to the indicator.
- Connection to the indicator and calibration
- CE-M 3000e or 3000+3000e approval.
- CE-M 6000e or 6000+6000e approval.
- High resolution models for internal factory use.
- CCATEX: ATEX certificate for each load cell
- DCATEX2GD: Declaration of ATEX conformity of whole PLATFORM + ATEX 2GD DINI ARGEO INDICATOR
- DCATEX3GD: Declaration of ATEX conformity of whole PLATFORM + ATEX 3GD DINI ARGEO INDICATOR
- Indicator support column.
- Steel carts.
- Raising frames.
- Belt and roller units to be applied on the loading surface (upon estimate).
- Special sizes and capacities (upon estimate).

Available versions

Code	l x w x h (mm)	Max (kg)	d (g)	d* HR (g)	CE-M* 3000e (g)	CE-M* 2x3000e (g)
TS3	230x330x93	3	0,5	0,1	1	--
TS6	230x330x93	6	1	0,2	2	1-2
TS15	230x330x93	15	2	0,5	5	2-5
TT6	330x330x93	6	1	0,2	2	1-2
TT15	330x330x93	15	2	0,5	5	2-5
TT30	330x330x93	30	5	1	10	5-10
TQ15	400x400x110	15	2	0,5	5	2- 5
TQ30	400x400x110	30	5	1	10	5-10

TQ60	400x400x110	60	10	2	20	10-20
TQ150	400x400x110	150	20	5	50	20-50
TM30	400x500x110	30	5	1	10	5-10
TM60	400x500x110	60	10	2	20	10-20
TM150	400x500x110	150	20	5	50	20-50
TC30	500x500x110	30	5	1	10	5-10
TC60	500x500x110	60	10	2	20	10-20
TC150	500x500x110	150	20	5	50	20-50
TL60	500x600x132	60	10	2	20	10-20
TL150	500x600x132	150	20	5	50	20-50
TL300	500x600x132	300	50	10	100	50-100
TX60	600x600x132	60	10	2	20	10-20
TX150	600x600x132	150	20	5	50	20-50
TX300	600x600x132	300	50	10	100	50-100
TG150	700x700x145	150	20	5	50	--
TG300	700x700x145	300	50	10	100	50-100
TG600	700x700x145	600	100	20	200	100-200

(*) These divisions are obtainable only with the relative options.

Code	Description
DINICAL1	Calibration service for platform up to 30 kg, connected to Dini Argeo weight indicator - NET PRICE
DINICAL2	Calibration service for platform from 31 to 1500 kg, connected to Dini Argeo weight indicator - NET PRICE

Legal for trade approval , class III or IIII, with Dini Argeo indicator (only at time of order)

HR calibration (high resolution) with Dini Argeo indicator (only at time of order)

Code	Description
THR	High Resolution (HR) model.

Options for ATEX version (only at time of order)

IP68 protection

Support columns for Dini Argeo indicators

Charts for mobile weighing applications

Raising Frame

Roller unit

Calibration service with Dini Argeo indicator (only at time of order)

CARACTERISTICI PRINCIPALE

Funcții cu un aluminiu aprobat "punct unic" celulă de sarcină în conformitate cu standardele OIML R60 cu protecție împotriva prafului și a stropilor de apă conform standardelor IP65 (350 Ohm rezistență de intrare).

Structură tubulară din oțel, cuptor la foc vopsit albastru, cu picioarele reglabile și nivelare.

Echipat cu satinat AISI 304 suprafață din oțel inoxidabil de încărcare.

Până la 15 Vdc sursa de alimentare.

Cablu ecranat legătură 3m cu conectori pentru conectarea la indicator.

OPȚIUNI DISPONIBILE LA MOMENTUL COMENZII

Conectarea la indicator și calibrare

CE-M 3000e sau 3000 + 3000e aprobare.

CE-M 6000e sau 6000 + 6000e aprobare.

Modele de înaltă rezoluție pentru uz intern.

OPȚIUNI PENTRU ATEX VERSION

Certificat ATEX pentru fiecare celulă de sarcină: CCATEX

DCATEX2GD: Declarație de conformitate ATEX a întregului PLATFORMA + ATEX 2GD DINI ARGEO INDICATOR

DCATEX3GD: Declarație de conformitate ATEX a întregului PLATFORMA + ATEX 3GD DINI ARGEO INDICATOR

ACCESORII

Coloană sprijin Indicator.

Cărucioare oțel.

Creșterea cadre.

Unități Belt și role să fie aplicat pe suprafața de încărcare (la estimare).

Dimensiuni speciale și capacități (asupra estimare).