DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Platforma cantarire TE inox



Producator: Dini Argeo - Italia Capacitate: 3kg - 300Kg Omologare: Disponibila in variante omologate si neomologate Dimensiune: 230x330mm, 330x330mm, 400x400mm, 400x500mm, 600x600mm Material platan: Inox Celule sarcina: O celula

Descriere

- Functions with an approved “single point” STAINLESS STEEL load cell according to OIML R60 standards with protection against dust and water splashes according to IP67 standards.
- Structure with tubulars, mechanics, trinkets and satined steel loading surface in AISI304 stainless steel.
- Fitted with adjustable STAINLESS steel feet with plastic resting surface and level.
- Up to 15 Vdc power supply.
- Shielded 3m connection cable with connectors for connection to the indicator.
- Connection to the indicator and calibration with CE-M 3000e single range or 3000e+3000e dual range approval.
- High resolution models for internal factory use.
- CCATEX: ATEX certificate for each load cell.
- DCATEXMECH: Declaration of conformity of the whole system composed of PLATFORM + JUNCTION BOX + LOAD CELLS (only if the platform is ordered without the weight indicator; otherwise, refer to the certifications available for the indicator to which it will be connected).

Available versions

Code	l x w x h (mm)	Max (kg)	d (g)	CE-M* 3000e (g)	CE-M* 2x3000e (g)	d* HR (g)
TSE3	230x330x93	3	0,5	1	--	0,2
TSE6	230x330x93	6	1	2	1-2	0,5
TSE15	230x330x93	15	2	5	2-5	1
TTE6	330x330x93	6	1	2	1-2	0,5
TTE15	330x330x93	15	2	5	2-5	1
TTE30	330x330x93	30	5	10	5-10	2
TQE15	400x400x110	15	2	5	--	1
TQE30	400x400x110	30	5	10	5-10	2
TQE60	400x400x110	60	10	20	10-20	5
TQE150	400x400x110	150	20	50	20-50	10
TME30	400x500x110	30	5	10	5-10	2
TME60	400x500x110	60	10	20	10-20	5
TME150	400x500x110	150	20	50	20-50	10

TXE60	600x600x132	60	10	20	10-20	5
TXE150	600x600x132	150	20	50	20-50	10
TXE300	600x600x132	300	50	100	50-100	20

(*) These divisions are obtainable only with the relative options.

Code	Description
DINICAL1	Calibration service for platform up to 30 kg, connected to Dini Argeo weight indicator - NET PRICE
DINICAL2	Calibration service for platform from 31 to 1500 kg, connected to Dini Argeo weight indicator - NET PRICE

Legal for trade approval , class III or IIII, with Dini Argeo indicator (only at time of order)

HR calibration (high resolution) with Dini Argeo indicator (only at time of order)

Code	Description
THR	High Resolution (HR) model.

IP68 protection

Options for ATEX version (only at time of order)

Support columns for Dini Argeo indicators

Charts for mobile weighing applications

Raising Frame

Roller unit

Code	Description
RF50X65I	Stainless steel roller unit with PVC ø 40 idle rollers and 75 mm pitch, on stainless steel frame. Dimensions 500x650 mm.

Calibration service with Dini Argeo indicator (only at time of order)

CARACTERISTICI PRINCIPALE

Funcții cu o celulă "singur punct" sarcină INOX conform standardelor OIML R60 cu protecție împotriva prafului și a stropilor de apă conform standardelor IP67.

Structura cu elemente tubulare, mecanica, brelocuri și suprafață de încărcare din oțel satinat din oțel inoxidabil AISI304.

Echipat cu picioare reglabile din oțel inoxidabil cu suprafata de odihnă plastic și nivel.

Până la 15 Vdc sursa de alimentare.

Cablu ecranat legătură 3m cu conectori pentru conectarea la indicatorul.

OPȚIUNI DISPONIBILE LA MOMENTUL COMENZII

Conectarea la indicator și calibrare cu CE-M 3000e gamă sau 3000e + 3000e unic de omologare gamă dublu.

Modele de înaltă rezoluție pentru uz intern.

OPȚIUNI PENTRU VERSIUNEA ATEX

CCATEX: certificat ATEX pentru fiecare celulă de sarcină.

DCATEXMECH: Declarație de conformitate a întregului sistem compus din PLATFORMĂ + JUNCTION BOX + CELULE DE SARCINĂ (numai dacă platforma este comandată fără indicator; altfel, vezi certificatele disponibile pentru indicatorul la care va fi conectată).