DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Platforma cantarire IKT



Producator: Kern & Sohn - Germania Capacitate: 3,1kg; 8,1kg; 10,1kg; 16,1kg; 30,1kg; 36,1kg; 60,1kg; 65,1kg; 101kg; 151Kg Omologare: Disponibil in variante neomologate Dimensiune: 228x228mm; 315x305mm; 450x350mm Material platan: Inox Celule sarcina: O celula

Descriere

- Convenient recipe weighing: 99 recipes each with 10 components can be stored in plain text (IKT-M: 5 recipes each with 7 components). If one recipe ingredient is more than it should be, then the practical back calculation function automatically calculates the new target weights of the other ingredients. The actual and target values and the proportional percentage can then be printed
- Multiplier function: recipes where the ingredients have been recorded as percentages can easily be multiplied up when you enter the new target weight, which is ideal for the production of larger containers, bulk packs etc.
- Rapid function for shortened stabilisation time with reduced resolution
- Control outputs (optocoupler, digital I/O) to connect relays, signal lamps, valves etc. (35 V / 80 mA)
- For particularly high counting accuracy, there is an option of combining the KERN IKT range with a high-precision reference balance to make a counting system, please enquire

Modes

Weighing

Counting

Dispensing

Recipe weighing

Checkweighing

Totalising with daily total

Percentage determination

Animal weighing

Surface weight

Density determination, only with , not for

Rapid function, not for

Functions

- Capacity display, with -
- Dispensing assistance (-/+), with ,
- Net/Gross display, permanently on, with -
- Variable reference quantity, with
- Automatic reference optimisation, with
- Tare deduction numerical or from the memory unit, with -
- Input of item or batch description, operator etc., with -
- Freely programmable weighing unit, e. g. display directly in special units such as length of thread g/m, paper weight g/m2, or similar, with
- Date/time, with -
- Statistical function, with
- GLP printout, with -
- Individual formatting of up to 16 printer forms, recipes, operating mode master data in MS Excel, Import using RS-232, for examples, see the internet.
- Ideal pentru realizare retete: 99 de retete, fiecare cu 10 de componente pot fi stocate în text simplu (modelul IKT-M: 5 retete, fiecare cu 7 componente).

În cazul în care un ingredient din reteta depaseste limita maxima, funcția de calcul preia automat noile greutăți proportional cu celelalte ingrediente.

- Funcția Multiplicator: retete unde ingredientele au fost înregistrate în procente pot fi ușor multiplicate (ideal pentru producerea de containere mari, cutii vrac etc.)
- Funcția rapidă pentru timpul de stabilizare, cu rezoluție redusă
- Ieșiri de control (optocuplor, I / O digitale) pentru a conecta relee, lămpi de semnalizare, supape etc. (35 V / 80 mA)
- Pentru precizie mare la numărare, există opțiunea de a combina gama KERN IKT cu un echilibru de referință de înaltă precizie pentru a face un sistem de numărare
- Moduri de functionare

- Cântar

- Calcul

- Rețete de cântărire

- Cântărire de control

- Totalizare zilnica

- Determinare Procentaj

- Functie antivibratie

- Determinare densitate

- Funcții

- Afișaj Capacitate, cu -

- Distribuire asistență (- / +),

- Afișare greutate neta / bruta,

- Cantitate de referință variabilă

- Data / ora

- Funcție statistică

- Imprimare GLP

- Formatare individuala de tichete cantaire pentru maxim 16 de imprimante (retete, export în MS Excel, Import folosind RS-232,etc...)

Item number	Weighing range [Max] kg	Read out [d] g	Verific. value [e] g	Repro-ducibi-lity g	Linea-rity g	Min. piece weight [Counting] g/piece
IKT 6K0.1	6	0,1		0,1	0,3	0,1
IKT 12K0.2	12	0,2		0,2	0,6	0,2
IKT 30K0.5	30	0,5		0,5	1	0,5

IKT 60K1L	60	1		1	2	1
IKT 120K2L	120	2		2	4	2
IKT 150K2XL	150	2		2	4	2
IKT 300K5XL	300	5		5	10	5
High-resolution display						
IKT 3K0.01S	3	0,01		0,02	0,05	0,01
IKT 8K0.05	8	0,05		0,05	0,15	0,05
IKT 10K0.1S	10	0,1		0,1	0,3	0,1
IKT 16K0.1	16	0,1		0,1	0,3	0,1
IKT 30K0.1	30	0,1		0,2	0,5	0,1
IKT 30K0.1L	30	0,1		0,2	0,3	0,1
IKT 36K0.2	36	0,2		0,2	0,6	0,2
IKT 36K0.2L	36	0,2		0,2	0,6	0,2
IKT 60K0.2L	60	0,2		0,4	0,6	0,2
IKT 65K0.5L	65	0,5		0,5	1,5	0,5
IKT 100K0.5L	100	0,5		0,5	2	0,5
IKT 150K1L	150	1		1	3	1
Note: For applications that require verification, please order verification at the same time, initial verification at a later date is not possible. Verification at the factory, we need to know the full address of the location of use.						
IKT 6K1M	6	1	1	0,5	0,5	1
IKT 12K2M	12	2	2	1	1	2
IKT 30K5M	30	5	5	2,5	2,5	5
IKT 60K10LM	60	10	10	5	5	10
IKT 120K20LM	120	20	20	10	10	20