DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Platforma cantarire SFE



Producator: Kern & Sohn - Germania Capacitate: 15kg, 30kg, 60Kg Omologare: Disponibil in variante neomologate si omologate Dimensiune: 300x240mm, 400x300mm Material platan: Inox Celule sarcina: O celula

Descriere

- Robust stainless steel display device, ideal for industrial applications, for easy and hygienic cleaning
- Load cells aluminium, silicone-coated. IP65: Protected against dust and water splashes
- Stainless steel weighing plate
- Painted steel base
- Stainless steel display KERN KFE-TM. Flexible positioning, eg. free-standing or mounted to the wall
- Weighing with tolerance range (checkweighing): Input of an upper/lower limit value. A visual and audible signal assists with portion division, dispensing or grading
- Vibration-free weighing: at the push of a button, a stable average weight is given when the environmental conditions are unstable
- PRE-TARE function for manual subtraction of a known container weight, useful for checking fill-levels (only for non-verified models)
- Dispozitiv de afișare robust din oțel inoxidabil, ideal pentru aplicații industriale, curățare ușoară și igienică
- Celule de sarcină din aluminiu, acoperite cu silicon. IP65: Protecție împotriva prafului și stropi de apă
- Placă de cântărire din oțel inoxidabil
- Bază din oțel vopsit
- Dispozitiv din oțel inoxidabil KERN KFE-TM. Poziționare flexibilă, de exemplu. de sine stătătoare sau montat pe perete
- Cântărire cu interval de toleranță (cântărire de control)
- Vibrații la cântărire: de la simpla apăsare a unui buton, o greutate medie stabilă este dată atunci când condițiile de mediu sunt instabile

Item number	Weighing range [Max] kg	Readout [d] g	Verification value [e] g	Minimum load [Min] g

Note: For applications that require verification, please order verification at the same time, initial verification at a later date is not possible. Verification at the factory, we need to know the full address of the location of use.				
SFE 100K-2LM	150	50	50	1000
SFE 100K-2M	150	50	50	1000
SFE 100K-2XLM	150	50	50	1000
SFE 10K-3LM	15	5	5	100
SFE 15K5IPM	15	5	5	100
SFE 300K-1LM	300	100	100	2000
SFE 30K10IPM	30	10	10	200
SFE 60K-2LM	60	20	20	400
SFE 60K20IPM	60	20	20	400
SFE 6K-3M	6	2	2	40