**DATA SPEED S.R.L.**
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

# Platforma cantarire RPLC




Producator: Dini Argeo - Italia Capacitate: 1,5kg - 15Kg Omologare: Disponibil in variante neomologate si omologate Dimensiune: 178mm diametru Material platan: Aluminiu Celule sarcina: O celula

## Descriere

- Functions with an approved aluminium “single point” load cell according to OIML R60 standards with protection against dust and water splashes according to IP65 standards (350 Ohm input resistance).
- Anodized blue aluminium structure with adjustable resting feet and level.
- Stainless steel plate.
- 15 Vdc power supply.
- Shielded 1,5 m connection cable with connectors for connection to the indicator.
- Connection to the indicator and calibration with CE-M 3000e approval.
- High resolution models for internal factory use.
- CCATEX: ATEX certificate for each load cell.
- DCATEXMECH: Declaration of conformity of the whole system composed of PLATFORM + JUNCTION BOX + LOAD CELLS (only if the platform is ordered without the weight indicator; otherwise, refer to the certifications available for the indicator to which it will be connected).

CARACTERISTICI PRINCIPALE

- Functii cu aliaj de aluminiu, avand celule de sarcina Single Point in conformitate cu standardele OIML R60, cu protectie impotriva prafului si a umiditatii IP65;
- Structura de aluminiu albastru anodizat cu picioare reglabile si la nivel;
- Platan din otel inoxidabil;
- 15Vdc alimentare electrica;
- Cablu ecranat de 1,5 m pentru conectarea la indicatori.

OPȚIUNI DISPONIBILE LA MOMENTUL COMENZII

- Conectarea la indicator și calibrare cu aprobare CE-M 3000e.
- Modele de înaltă rezoluție pentru uz intern.