**DATA SPEED S.R.L.**
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

# Sauter TB-masoara grosimea invelisului




Aparat digital de masurare a grosimii invelisului Producator: Sauter - Germania Capacitate: 1.000µm; 2.000µm Precizie: 0,1µm

## Descriere

- External sensor for difficult-to-access measurements
- Base plate and calibration foils included
- Delivered in a hard carrying case
- Offset-Accur: This function allows you to adjust the instrument precisely on the locally measured range by a two-point calibration. This results in a superior accuracy of approx. 1 % of the measured value
- SAUTER TB 2000-0.1F.: Specifically designed for the automobile industry
- Selectable measuring units: µm, inch (mil)
- Auto-Power-Off

Senzor extern pentru gazde-la-acces masuratori

Placa de bază și de calibrare folii incluse

Livrat într-un caz greu care transportă

Offset-Accur: Această funcție vă permite să reglați instrumentul tocmai pe intervalul măsurat la nivel local de către o calibrare în două puncte. Acest lucru duce la o precizie superioară de aprox. 1% din valoarea măsurată

SAUTER TB 2000-0.1F .: Conceput special pentru industria de automobile

Unități de măsură selectabile: pm, inch (MIL)

Auto-Power-Off.

| Item number | Test object | Measuring range [Max] µm | Readout [d] µm | Smallest sample surface convex mm (radius) | Smallest sample surface concave mm (radius) |
|---|---|---|---|---|---|
| TB 1000-0.1F. | Coatings on steel and iron | 1000 | 0,1 1 | 1,5 | 25 |
| TB 1000-0.1N. | Insulating coatings on non-magnetic metals | 1000 | 0,1 1 | 1,5 | 25 |
| TB 1000-0.1FN. | Combination instrument: F, N | 1000 | 0,1 1 | 1,5 | 25 |
| TB 2000-0.1F. | Non-magnetic coatings on iron, steel | 2000 | 0,1 1 | 3 | 50 |