DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Aparat - Sauter TC



Producator: Sauter - Germania Capacitate: 1.250µm Precizie: 0,1µm

Descriere

- Ergonomic design for easy handling
- Data interface RS-232, included
- Base plate and calibration foils included
- Delivered in a hard carrying case
- Offset-Accur: This function allows you to adjust the instrument precisely on the locally measured range by a two-point calibration. This results in a superior accuracy of approx. 1 % of the measured value
- Selectable measuring units: µm, inch (mil)

SAUTER TC 1250-0.1FN-CAR.:

- Specifically designed for the automobile industry
- Automatic recognition of measuring mode (F or N): "point and shoot"
- Simple and convenient 1-key operation

Design ergonomic pentru o manevrare ușoară

Interfață de date RS-232, inclus

Placa de bază și de calibrare folii incluse

Livrat într-un caz greu care transportă

Offset-Accur: Această funcție vă permite să reglați instrumentul tocmai pe intervalul măsurat la nivel local de către o calibrare în două puncte. Acest lucru duce la o precizie superioară de aprox. 1% din valoarea măsurată

Unități de măsură selectabile: pm, inch (MIL)

SAUTER TC 1250-0.1FN-CAR .:

Conceput special pentru industria de automobile

Recunoașterea automată a modului (F sau N) de măsurare: "punct și trage"

Simplu și convenabil de operare 1-cheie.

Item number	Test object	Measuring range [Max] µm	Readout [d] µm	Smallest sample surface convex mm (radius)	Smallest sample surface concave mm (radius)

TC 1250-0.1F.	Coatings on steel and iron	1250	0,1 1	1,5	25
TC 1250-0.1N.	Insulating coatings on non-magnetic metals	1250	0,1 1	3	50
TC 1250-0.1FN.	Combination instrument: F / N	1250	0,1 1	1,5	25
TC 1250-0.1FN-CAR.	Combination instrument: F / N	1250	0,1 1	1,5	25