DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Stand - Sauter TI



Producator: Sauter - Germania Teste: HBD

Descriere

- For Shore hardness testing of plastics, leather etc.
- Glass plate: Providing a higher base hardness and superior accuracy
- Mechanical construction: Robust design for precise measuring
- Level adjustment: For the precise levelling of the base plate blate
- Adjustable base plate for the correction of inhomogeneous test objects
- Operation:
  - 1. The SAUTER hardness testing device HB is fitted in a suspended position
  - 2. The test object is placed on the round testing table right under the durometer pin
  - 3. By lowering the handle lever, the measurement instrument is pressed in a controlled manner into the test object
- The accuracy of the displayed result is approx. 25 % higher than in a manual operated test

Pentru Shore testarea duritate de material plastic, piele, etc.

Placă de sticlă: Asigurarea o duritate de bază mai mare și precizie superioară

Construcție mecanică: Design robust pentru măsurare precisă

Reglarea nivelului: Pentru nivelarea exactă a blate placa de bază

Placă de bază reglabil pentru corectarea obiectele de testare neomogene

Funcționare:

1. duritate SAUTER dispozitiv de testare HB este montat într-o poziție suspendată 2. Obiectul testat este plasat pe masa de testare rotundă chiar sub PIN-ul durometru 3. Prin scăderea maneta mâner, instrumentul de măsură este apăsat într-o manieră controlată în obiectul testat

Precizia rezultatul afisat este de aprox. 25% mai mare decât într-un manual operat de testare.

Item number	Suitable for
TI-A0	HBA, HB0
TI-D.	HBD