DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Platforma IEX-EU



Platforma IEX-EU Producator: Kern

Descriere

- The range has European ATEX approval: II 2 G IIB T4 for use in hazardous industrial environments in zone 1, where there is explosion danger, e.g. through handling of flammable substances, which are present in high concentrations in the form of gas, mist or vapour
- Especially suitable for:
  - Paint industry
  - Chemistry/Petrochemical industry
  - Cosmetics industry
  - Plastics production
- Stainless steel weighing plate, substructure in wing design, steel, lacquered
- Load cells: aluminium, silicone-coated, dust and spray protection IP65
- Robust stainless steel display device, protected against dust and water splashes (IP67)
- Benchtop stand/wall mount for display device as standard
- Power supply through a power source outside the explosion-proof area. 20 m long cable with ATEX-approved screw coupling (II 2 G IIB T4) to fix the display device and fixed mains adapter

Gama are aprobare ATEX european: II 2 G IIB T4 pentru utilizarea în medii industriale periculoase în zona 1, în cazul în care există pericol de explozie, de exemplu, prin manipularea substanțelor inflamabile, care sunt prezente în concentrații mari în formă de gaz, vapori sau vapori

Adecvat în special pentru:

- Industria vopselelor
- Chimie / Petrochimie
- Industria cosmeticelor
- Producția de materiale plastice

Otel inoxidabil de cântărire placă, infrastructura în proiectarea aripa, oțel, lăcuit

Celulele de încărcare: aluminiu, acoperite cu silicon, praf și protecție IP65 pulverizare

Robust inoxidabil dispozitiv de afișare oțel, protejat împotriva prafului și a stropilor de apă (IP67)

Mount Benchtop suport / perete pentru dispozitivul de afișare standard

Sursa de alimentare printr-o sursă de alimentare afara careului, rezistent la explozii. 20 m de cablu lung cu cuplare aprobat-ATEX șurub (II 2 G IIB T4) pentru a fixa dispozitivul de afișare și de rețea fixe adaptor

Item number	Weighing range [Max] kg	Readout [d] g	Verific. value [e] g	Repro-ducibi-lity g	Linea-rity g	Option Verification	Option DAkkS Calibration Certificate
IEX 6K-3MEU	6	2	2	2	2	965-228	963-128
IEX 10K-3MEU	15	5	5	5	5	965-228	963-128
IEX 30K-2MEU	30	10	10	10	10	965-228	963-128
IEX 60K-2MEU	60	20	20	20	20	965-229	963-129
IEX 100K-1MEU	150	50	50	50	50	965-229	963-129