DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Indicator Cantarire 3590EQ QWERTY



Indicator Cantarire 3590EQ QWERTY , indicator de greutate evoluat odată cu QWERTY INTEGRAT KEYBOARD. Producator: Dini Argeo.

Descriere

.

- 59-key QWERTY and functional alphanumerical waterproof keyboard.
- Highly efficient BLU LED display with digits 15mm high. Configurable screens.
- Blue backlit LCD graphic 25x100mm display.
- Easy to clean ABS waterproof IP65 enclosure; resistant to harsh and corrosive environments.
- Dimensions: 279x124x187mm.
- Suitable for use on the table, column, or wall.
- Real time clock and permanent data storage.
- Fitted alibi memory, integrated on the motherboard.
- Functions available with DINITOOLS utility - Configuration, calibration, data entry and print formatting. - Recording and filing of all the information on PC. - Complete retrieval of the data saved for quick substitution. - Instrument calibration with numeric values.
- Selection of the programme language directly in the set-up.
- 24-bit A/D converter, 4 channels, up to 3200 conv./sec. and up to 8 signal linearisation points.
- 2 independent analogue channels for reading of the weight.
- Connection with up to 16 analogue load cells of 350 Ohm (45 load cells of 1000 Ohm) and with the main digital load cells available on the market.
- Up to 10.000e OIML or 3 x 3000e @ 0,3 µV/d CE-M legal for trade.
- Up to 1.000.000 displayable divisions for internal factory use, with internal resolution up to 3.000.000 points.
- Connectable to printers and labellers with the command drivers.
- 110-240 Vac power supply; built-in rechargeable battery for use in prolonged absence of the power mains.
- EC Type Approval (EN45501)
- OIML R76

.

Available versions

Optional power supply cords

Junction Box / Boards - Cell cables

Legal for trade approval
Storing the weighs (only at time of order)
Printers/Labellers
Communication Interfaces
Connection cables
Input/Output
Attached control light box
Weight repeaters
Columns, supports brackets, visors
PC keyboard / Scanner / Connection cables
Options for ATEX version
Protection against electric discharges
Remote control
.

Detalii