DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Indicator Cantarire 3590EXP ENTERPRISE



Indicator Cantarire 3590EXP ENTERPRISE , INDICATOR greutate pentru aplicații avansate INDUSTRIALE, în ABS IP65. Producator: Dini Argeo.

Descriere

.

- 25-key alphanumerical waterproof keyboard.
- Highly efficient red led display with 6 digits 15mm high.
- Backlit LCD graphic 25x100mm display.
- Synoptic bar graph with 16 bright LEDs showing the active functions.
- Easy to clean ABS waterproof IP65 enclosure; resistant to harsh and corrosive environments.
- Dimensions: 278x125x186 mm.
- Suitable for use on the table, column or wall.
- Real time clock and permanent data storage.
- Fitted alibi memory, integrated on the motherboard.
- Functions available with DINITOOLS utility - Configuration, calibration, data entry and print formatting. - Recording and filing of all the information on PC. - Complete retrieval of the data saved for quick substitution. - Instrument calibration with numeric values.
- Selection of the programme language directly in the set-up.
- 24-bit A/D converter, 4 channels, up to 3200 conv./sec. and up to 8 signal linearisation points.
- 4 independent analogue channels (up to 2 in the E-AF03 version, 1 in the E-AF09 version) for reading of the weight.
- Connection with up to 16 analogue load cells of 350 Ohm (45 load cells of 1000 Ohm) and with the main digital load cells available on the market (mod. E-AF03).
- Up to 10.000e OIML or 3 x 3000e @ 0,3 µV/d CE-M legal for trade.
- Up to 1.000.000 displayable divisions for internal factory use, with internal resolution up to 3.000.000 points.
- Power supply: 3590E version: 12 Vdc via external power supply. All other versions: 110-240 Vac and built-in rechargeable battery.
- Connectable to printers and labellers with the command drivers.
- Available in "P" version, fitted with attached printer as standard.
- EC Type Approval (EN45501)
- OIML R76
- OIML R51 - MID
- OIML R134 (AF09)
- AF01: Totalization and formula weighing
- AF02: Pieces/quantity counting

- AF03: Weighbridges - Input/Output vehicle
- AF04: Statistical checking of prepackaged goods
- AF05: Price compunting and industrial labelling
- AF08: Wheel and axle static weighing with 2 or various platforms
- BATCH1: Single product dosage systems in loading and unloading

Full version with 2 inputs, 4 outputs and RS485

Specific versions

Available firmwares

Optional power supply cords

Junction Box / Boards - Cell cables

Legal for trade approval

Storing the weighs (only at time of order)

Printers/Labellers

Communication Interfaces

Digital Input/Output

Connection cables

Attached control light box

Weight repeaters

Columns and supports brackets

Options for ATEX version

PC keyboard / Scanner / Connection cables

Protection against electric discharges

Keyboard protection cover

Remote control

.

Detalii: