DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Indicator Cantarire 3590EKR ENTERPRISE



Indicator Cantarire 3590EKR ENTERPRISE, Indicator de greutate cu carcasa de transport pentru aplicații industriale. Producator: Dini Argeo.

Descriere

.

- ABS transport case, with housing for the indicator and space for extra accessories.
- 3590EXP series indicator fit in a metallic rack type involucre with dimensions of 270x440mm, complete of housing for optional printer, connectors for platforms, and serial output on 9-pole connector.
- Dimensions: 325x460x170 mm. Weight: about 5 kg.
- 25-key alphanumerical waterproof keyboard.
- Highly efficient red led display with 6 digits 15mm high.
- Backlit LCD graphic 25x100mm display.
- Synoptic bar graph with 16 bright LEDs showing the active functions.
- Permanent time/date and data storage.
- Fitted with alibi memory.
- Functions available with the DINITOOLS utility: - Configuration, calibration, data entry and print formatting. - Recording and filing of all the information on PC, complete with the calibration data of each instrument. - Complete retrieval of the data saved for quick substitution. - Instrument calibration with numeric values.
- Selection of the programme language directly in the set-up.
- 24-bit A/D converter, 4 channels, up to 3200 conv./sec. and up to 8 signal linearisation points.
- Up to 10.000e OIML or 3 x 3000e @ 0,3 µV/d CE-M legal for trade.
- Up to 1.000.000 displayable divisions for internal factory use, with internal resolution up to 3.000.000 points.
- Fitted with 4 connectors for connection to 4 platforms (up to 2 in the 3590EKR03P model, up to 1 in the 3590EKR09P model).
- Connectable with up to 16 analogue 350-Ohm (or 45 1000-Ohm) load cells.
- Connectable with the main digital load cells available on the market.
- Built-in rechargeable battery (10-hour minimum operating time, recharge in 8 hours) with fitted external 12 Vdc / 230 Vac adapter.
- All versions are fitted with attached thermal printer.
- EC Type Approval (EN45501)
- OIML R76
- OIML R51 - MID

- OIML R134 (AF09)
- AF01: Totalization and formula weighing
- AF02: Pieces/quantity counting
- AF03: Weighbridges - Input/Output vehicle
- AF04: Statistical checking of prepackaged goods
- AF05: Price compunting and industrial labelling
- AF08: Wheel and axle static weighing with 2 or various platforms
- AF09: Dynamic and static axle weighing with 2 platforms

- wizards, operator messages
- serial port management, protocols customization
- digital I/O full management
- sequential or simultaneous automations
- data entry, custom archives

Dini Argeo can offer the service of custom development programs.

Available firmwares

Junction Box / Boards - Cell cables

Legal for trade approval

Storing the weighs (only at time of order)

Printers/Labellers

Input/Output

Communication Interfaces

Weight repeaters

Connection cables

PC keyboard / Scanner / Connection cables

Remote control

.

Detalii: