DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Indicator Cantarire CPWET Enterprise



Indicator Cantarire CPWET Enterprise , indicator greutate pentru aplicatii avansate, industriale, IP68 INOX. Producator: Dini Argeo.

Descriere

.

- Waterproof 25-key numerical functional keyboard.
- Programmable function keys, for customising the keyboard functions according to the needs.
- Easy to consult backlit graphic LCD display, with a clear visualisation of the weight and wide range of information.
- Fitted with 3-way control light made up to sinoptic bar-graph with 3 groups of 3 Leds each, to tollerance check and setpoint.
- IP68 stainless steel waterproof case, easy to clean and resistant in harsh and corrosive environments.
- Dimensions, including support bracket: 269x58,8x183mm.
- Suitable for use on the table, or wall.
- Real time clock and permanent data memory.
- Integrated alibi memory for CE-M communication with PC and printer.
- Functions available with DINITOOLS utility - Configuration, calibration, data entry and print formatting. - Recording and filing of all the information on PC. - Complete retrieval of the data saved for quick substitution - Instrument calibration with numeric values.
- Selection of the programme language directly in the set-up.
- A/D 24 bit sigma-delta 4-channel conversion, up to 200 conv./sec. with automatic selection. Filtering system through programmable software, adjustable according to the system.
- Calibration and Set-Up parameters, configurable from PC with Dinitools or with the keyboard; theoretical calibration with the entry of the characteristics of the load cells.
- Up to 1.000.000d displayable for internal factory use.
- Up to 10.000e or multirange 3 x 3000e @ 0,3 µV/d in CE-M approved version for legal for trade use.
- Up to 8 signal linearisation points with DINITOOLS.
- Internal resolution of up to 3.000.000 points.
- 12 Vdc power supply with external power adapter.
- Management of a weighing system with digital equalisation of the 4 cells or management of up to 4 independent weighing systems (depending on the application software).
- Connectable with up to 16 analogue load cells with 350 Ohm input resistance (45 1000 Ohm cells) and to the main digital load cells available on the market.

- Connectable to printers and labellers through the available command drivers.
- EC Type Approval (EN45501)
- OIML R76
- OIML R51 - MID
- AF01: Totalization and formula weighing
- AF02: Pieces/quantity counting
- AF03: Weighbridges - Input/Output vehicle
- AF04: Statistical checking of prepackaged goods
- AF05: Price compunting and industrial labelling
- AF09: Dynamic and static axle weighing with 2 platforms
- BATCH1: Single product dosage systems in loading and unloading

- wizards, operator messages
- serial port management, protocols customization
- digital I/O full management
- sequential or simultaneous automations
- data entry, custom archives

Dini Argeo can offer the service of custom development programs.

Available firmwares

Junction Box / Boards - Cell cables

Approval

Storing the weighs (only at time of order)

Printers/Labellers

Communication Interfaces

Connection cables

Input/Output

Weight repeaters

PC keyboard / Scanner / Connection cables

Options for ATEX version

Remote control

.

Detalii: