DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Indicator Cantarire DFWLB



Indicator Cantarire DFWLB, multifunctional IP68 greutate indicator pentru industrie. Producator: Dini Argeo.

Descriere

.

- 5-key functional waterproof keypad.
- Backlit 25mm LCD display with 6 high contrast digits with icons for showing the active functions.
- Easy to clean ABS IP68 case, resistant to harsh and corrosive environments.
- Suitable for use on the table, column, or wall.
- Fitted with fixing bracket with adjustable inclination.
- A/D 24 bit, 4 channel converter, max. 200 conv./sec. autoselect, and up to 8 signal linearisation points.
- Up to 10.000e or multirange 3 x 3000e @ 0,3 µV/d in CE-M approved versions for legal for trade use.
- Up to 1.000.000 displayable divisions with internal resolution up to 3.000.000 points.
- Connection with up to 8 load cells with input resistance equal to 350 Ohm or up to 16 cells of 700 Ohm each.
- Digital calibration and Set-Up from keypad or from PC through DINITOOLS.
- Power supply through built-in rechargeable battery, with 60h operating time, and fitted with external 12Vdc battery charger.
- EC Type Approval (EN45501)
- OIML R76
- MAIN FUNCTIONS: - Zeroing - Automatic tare - Presettable tare - Printing in 1, 2 or 3 copies - Data transmission to PC.
- OPERATING MODES: - High Resolution Weighing x 10 - Net/Gross or lb/kg conversion - Accumulation - Formula weighing - +/- Checkweighing - Percentage weighing - Approved transmission of the weight to PC/PLC or data recording on MMC/USB (with Alibi memory ALMEM option) - Counting - In/Out Truck weighing - Hold and Peak.
- RS232/C bidirectional port on RJ connector for quick connection (optional RS485) on screw terminal, configurable for PC, PLC, or additional remote display.
- RS232/C bidirectional port configurable for connection to printer or labeller.

Code	Description
DFWLB-1	IP68 weight indicator with built-in rechargeable battery. ABS case, 5-key keypad, backlit LCD display.

Approval
Junction Box / Boards - Cell cables
Storing the weighs (only at time of order)
Printers/Labellers
Communication Interfaces
Connection cables
Date&Time option
Columns, supports brackets, visors
Weight repeaters
Remote control
Weight repeater software
Options for ATEX version
.

Detalii: