DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Indicator Cantarire DFWLID



Indicator Cantarire DFWLID, indicator de greutate inox cu Afisaj LCD cu cifre mari. Producator: Dini Argeo.

Descriere

.

- 5-key functional waterproof keypad.
- Backlit 40mm LCD display with 6 high contrast digits with icons for showing the active functions.
- Color and brightness of the backlighting, customizable from Setup.
- Easy to clean stainless steel IP68 case, resistant to harsh and corrosive environments.
- Dimensions: 243x145x78,4mm.
- Suitable for use on the table, column, or wall.
- A/D 24 bit, 4 channel converter, max. 200 conv./sec. autoselect, and up to 8 signal linearisation points.
- Up to 10.000e or multirange 3 x 3000e @ 0,3 µV/d in CE-M approved versions for legal for trade use.
- Up to 1.000.000 displayable divisions with internal resolution up to 3.000.000 points.
- Connection with up to 8 load cells with input resistance equal to 350 Ohm or up to 16 cells of 700 Ohm each.
- Digital calibration and Set-Up from keypad or from PC through DINITOOLS.
- Power supply through built-in rechargeable battery, with 40h operating time, and fitted with external battery charger.
- MAIN FUNCTIONS: - Zeroing - Automatic tare - Presettable tare - Printing in 1, 2 or 3 copies - Data transmission to PC.
- OPERATING MODES: - High Resolution Weighing x 10 - Net/Gross or lb/kg conversion - Accumulation - Formula weighing - +/- Checkweighing - Percentage weighing - Approved transmission of the weight to PC/PLC (with Alibi memory ALMEM option) - Counting - In/Out Truck weighing - Hold and Peak.
- RS232/C bidirectional port on RJ connector for quick connection (or optional RS485) on screw terminal, configurable for PC, PLC, or additional remote display.
- RS232/C bidirectional port configurable for connection to printer or labeller.

Code	Description
DFWLID-1	Weight indicator with battery and external power supply. IP68 stainless steel case, 40mm LCD display with color backlit, and 5 waterproof keys.
DFWLIP	Weight indicator with internal power supply. IP68 stailess steel case with 40mm LCD display with color backlit and 5 waterproof keys.

Junction Box / Boards - Cell cables
Approval
Storing the weighs (only at time of order)
Printers/Labellers
Communication Interfaces
Connection cables
Weight repeaters
Date&Time option
Columns and supports
Options for ATEX version
Remote control
.

Detalii: