DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Indicator Cantarire DFWR



Indicator Cantarire DFWR, Indicator cu foarte luminos afisaj rosu. Producator: Dini Argeo.

Descriere

.

- Waterproof 17-key functional keyboard.
- Very bright red LED display with 6 digits 25 mm high; easily visible from all angles and from long distances, with adjustable brightness intensity.
- Complete of 6 Leds for showing the active functions.
- Waterproof ABS IP65 case, easy to clean and resistant to harsh and corrosive environments.
- Dimensions in mm: 278x125x186.
- Suitable for use on the table, column, or wall.
- Fitted with attached thermal printer and real time clock in the DFWRP version.
- A/D 24 bit, 4 channel converter, up to 200 conv./sec. autoselect, and up to 8 signal linearisation points.
- Up to 10.000e or multirange 3 x 3000e @ 0,3 µV/d in CE-M approved version for legal for trade use.
- Up to 800.000 divisions displayable with built-in resolution up to 3.000.000 points.
- Calibration and digital Set-Up from the keyboard or from PC with DINITOOLS.
- Built-in rechargeable battery (60 hours with a 350 Ohm load cell) and internal 110-240 Vac adapter.
- Connection with up to 8 load cells having an input resistance of 350 Ohm or with up to 16 cells of 700 Ohm.
- EC Type Approval (EN45501)
- OIML R76
- RS232/C port configurable for connection with printer/labeller, or for attached printer.
- RS232/C (or optionally RS485) bi-directional port configurable for PC, PLC, remote display, and radio modem. Quick RJ RS232 plug connection.
- KEYBOARD: Zeroing, Automatic tare, Presettable tare, printing and/or data transmission, selectable function command, on/off switching, Database of 10 tares, 2 Numeric IDs, keyboard lock, repetition of last printout made.
- SELECTABLE FUNCTIONS: - High Resolution Weighing x 10. - Net/Gross or lb/kg conversion. - Accumulation. - Formula weighing. - +/- Checkweighing. - Percentage weighing. - Approved transmission of the weight to PC/PLC or data recording on MMC/USB (with Alibi memory ALMEM option). - Counting(Max. resolution of 1.500.000 divisions). - In/Out Truck weighing. - Hold and Peak. - Set Point Control (with DFIO option).
- Infrared 19-key remote control: zero, tare / manual tare, enable / disable function, print, switch-off.
- Radiofrequency 6-key remote control: zero, tare, enable / disable function, print, switch-off.

Code	Description
DFWRXPCC	Indicator with red LED display. IP65 ABS case, 17-key keypad, and standard weighing programme.
DFWRPXPCC	Indicator with red LED display, printer and real time clock. IP65 ABS case, 17-key keypad, LED display, and standard weighing programme.

Optional power supply cords

Approval

Junction Box / Boards - Cell cables

Printers/Labellers

Storing the weighs (only at time of order)

Communication Interfaces

Connection cables

Control light

Options for ATEX version

Weight repeaters

Date&Time option

Columns and supports

Keyboard protection cover

Remote control

.

Detalii: