DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Indicator Cantarire DFW Atex 2GD



Indicator Cantarire DFW Atex 2GD, indicator greutate pentru ATEX 1 si zona 21. Producator; Dini Argeo.

Descriere

.

- Waterproof 17-key numerical and functional keyboard.
- LCD display with 6 25-mm high contrast digits, clearly visible even in poor lighting conditions and with low temperatures, and with 6 LEDs for showing the active functions.
- Satined IP68 stainless steel case.
- Dimensions 264x174x115mm.
- Suitable for use on the table, or wall.
- Up to 10.000e or multirange 3 x 3000e @ 0,3 µV/d in CE-M approved version for legal for trade use.
- Up to 100.000 displayable divisions with internal resolution up to 3.000.000 points.
- Up to 8 signal linearization points with DINITOOLS (3 from keypad).
- A/D 24-bit sigma-delta conversion, up to 200 conv./sec. autoselect.
- Digital calibration and set-up from keyboard; Instrument management & configuration from PC with DINITOOLS.
- Power supply through external module: with DFWPBP76-ATEX optional battery pack; or with optional power adapter connectable to mains at 230 Vac or at 24 Vdc.
- Connection with up to 4 load cells having 350 Ohm input resistance.
- Fiber optic bidirectional port for connection with printer, labeller, PC, or PLC in safe area.
- 4 logic inputs and 4 barriered digital outputs, connectable to other intrinsic safety devices in a hazardous area.
- SCALE FUNCTIONS -Zeroing - Automatic Tare - Presettable Tare - ID1 and ID2 10-digit Codes - Print and data transmission commands - selectable function command - on/off switching.
- SELECTABLE FUNCTIONING MODES- High Resolution Weighing x 10-Net/Gross or lb/kg conversion- Accumulation- Formula weighing- +/- Checkweighing- Counting (Max. resolution of 1.500.000 divisions). - In/Out Truck weighing- Hold- Peer-to-peer (up to 4 remote connectable indicators). - Set Point Control (only in the DFWATEX2GDIO version combined with PW200XRDxxx and PW200IO options). - MODBUS serial protocol.

Approval kit

Declaration of ATEX conformity of whole

ATEX battery and battery charger
Intrinsically safe ATEX power supplier
Optical fibres and converter
NOTE: cables for the connection to peripheral devices upon request. Communication interfaces
Saving of the weighs
Columns and brackets
Other accessories
DFWATEX2GDIO: Application example:
.

Detalii: