DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Indicator Cantarire DFW Atex 3GD



Indicator Cantarire DFW Atex 3GD, indicator greutate pt. zona 22 si atex 2. Producator: Dini Argeo.

Descriere

.

- Waterproof 17-key functional keypad.
- Backlit LCD display with 6 25-mm high contrast digits and with indication of active functions.
- Satined IP68 stainless steel case.
- Suitable for use on the table, or wall.
- Dimensions: 264x174x115mm.
- Up to 10.000e or multirange 3 x 3000e @ 0,3 µV/d in CE-M approved version for legal for trade use.
- Up to 800,000 displayable divisions for internal factory use.
- Up to 8 signal linearization points with DINITOOLS (3 from keypad).
- Internal resolution up to 3.000.000 points.
- A/D 24-bit sigma-delta conversion, up to 200 conv./sec. autoselect.
- Board protection case inside the box.
- Digital calibration and set-up from keyboard.
- Instrument management & configuration from PC with DINITOOLS.
- 4 channels (for single weighing system).
- Power supply: DFWATEX3GD: through 110-240Vac internal power adapter; DFWATEX3GDB: through optional external battery (BP6ESTATEX3GD code), rechargeable in safe area.
- Connection with up to 8 load cells with 350 Ohm input resistance.
- EC Type Approval (EN45501)
- OIML R76
- RS232/C port configurable for connection to printer/labeller in safe zone.
- RS232/C (or optionally RS485) bi-directional port configurable for PC, PLC, additional remote display, in safe zone.
- KEYBOARD: Zeroing, Automatic tare, Presettable tare, printing and/or data transmission, selectable function command, on/off switching, database of 10 tares, 2 Numeric IDs, keyboard lock, repetition of last printout made.
- SELECTABLE FUNCTIONS: - High Resolution Weighing x 10. - Net/Gross or lb/kg conversion. - Accumulation. - Formula weighing. - +/- Checkweighing. - Percentage weighing. - Approved transmission of the weight to PC/PLC (with Alibi memory ALMEM option). - Counting(Max. resolution of 1.500.000 divisions). - In/Out Truck

weighing. - Hold. - Set Point Control (with DFIO option).

- Real time clock.
- Alibi memory with real time clock.
- Board module with 2 inputs + 2 setpoints (up to 2 connectable boards).
- RS485 interface.
- Ethernet interface.
- 0-10 or from 0 to 20mA analogue output with 16bit D/A converter.
- 24 Vdc power supply (ask for price estimate). TAKE NOTE:All the cables must be installed and protected according to the standards for electrical equipment.

Code	Description
DFWATEX3GD	IP68 stainless steel, ATEX 3GD indicator with internal power adapter. 17-key keypad, LCD backlit display, and standard weighing programme. Protection: ATEX II 3G Ex nR IIC T6 Gc X for gases and ATEX II 3D Ex tc IIIC T130°C Dc IP68 X for dust. Complete with manual and ATEX CE Conformity declaration, available in EN, DE, FR, and IT.
DFWATEX3GDB	ATEX 3GD indicator, to be combined always with BP6ESTATEX3GD option. IP68 stainless steel case, 17-key keypad, LCD backlit display, and standard weighing programme. Protection: ATEX II 3G Ex nR IIC T6 Gc X for gases and ATEX II 3D Ex tc IIIC T130°C Dc IP68 X for dust. Complete with manual and ATEX CE Conformity declaration, available in EN, DE, FR, and IT.

Options only available at time of order

Accessories

.

Detalii;