DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Indicator Cantarire DFW Atex 3D



Indicator Cantarire DFW Atex 3D, indicator greutate Atex pentru zona 22. Producator; Dini Argeo.

Descriere

.

- Waterproof 17-key functional keypad.
- Backlit LCD display with 6 25-mm high contrast digits and with indication of active functions.
- Satined IP65 stainless steel case.
- Suitable for use on the table, or wall.
- Dimensions: 264x174x115mm.
- Up to 10.000e or multirange 3 x 3000e @ 0,3 µV/d in CE-M approved version for legal for trade use.
- Up to 800,000 displayable divisions for internal factory use.
- Up to 8 signal linearization points with DINITOOLS (3 from keypad).
- Internal resolution up to 3.000.000 points.
- A/D 24-bit sigma-delta conversion, up to 200 conv./sec. autoselect.
- Board protection case inside the box.
- Digital calibration and set-up from keyboard.
- Instrument management & configuration from PC with DINITOOLS.
- 4 channels (for single weighing system).
- 110-240 Vac power supply through fitted internal power adapter or fitted 6V 4,5Ah battery, rechargeable in safe zone.
- Connection with up to 8 load cells with 350 Ohm input resistance.
- EC Type Approval (EN45501)
- OIML R76
- RS232/C port configurable for connection to printer/labeller in safe zone.
- RS232/C (or optionally RS485) bi-directional port configurable for PC, PLC, additional remote display, in safe zone.
- KEYBOARD: Zeroing, Automatic tare, Presettable tare, printing and/or data transmission, selectable function command, on/off switching, database of 10 tares, 2 Numeric IDs, keyboard lock, repetition of last printout made.
- SELECTABLE FUNCTIONS: - High Resolution Weighing x 10. - Net/Gross or lb/kg conversion. - Accumulation. - Formula weighing. - +/- Checkweighing. - Percentage weighing. - Approved transmission of the weight to PC/PLC (with Alibi memory ALMEM option). - Counting(Max. resolution of 1.500.000 divisions). - In/Out Truck

weighing. - Hold. - Set Point Control (with DFIO option).

- Real time clock.
- Alibi memory with real time clock.
- Board module with 2 inputs + 2 setpoints (up to 2 connectable boards).
- RS485 interface.
- Ethernet interface.
- 0-10 or from 0 to 20mA analogue output with 16bit D/A converter.
- 24 Vdc power supply (ask for price estimate). TAKE NOTE:All the cables must be installed and protected according to the standards for electrical equipment.

Code	Description
DFWATEX3D	IP65 stainless steel ATEX 3D indicator. 17-key keypad, LCD backlit display, and standard weighing programme. Protection mode: ATEX II 3D Ex tc IIIC T130°C Dc IP65 X for dust. Complete with manual and DECLARATION OF CONFORMITY. The manuals and ATEX CE CONFORMITY DECLARATIONS are available in EN, DE, FR, and IT.

Options only available at time of order

Accessories

.

Detalii: