DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Indicator Cantarire DGTQF



Indicator Cantarire DGTQF, microcontrolere pentru sisteme dozate. Producator : Dini Argeo.

Descriere

.

- Easy to use 5-key waterproof keyboard.
- Highly efficient red LED display with 6 13-mm digits and 6 LEDs for showing active functions.
- Case for panel mounting in Abs according to DIN standard, 96x96x80mm (lxhxp). Perforation 90x88 mm (lxh) for panel mounting.
- A/D 24-bit sigma-delta conversion with 4 channels, up to 200 conv./sec. autoselect.
- Management of a weighing system from 1 to 4 channels (cells) with digital equalization.
- Connectable with up to 16 analogue load cells with 350 Ohm input resistance.
- Up to displayable 1.000.000d with internal resolution up to 3.000.000 points.
- Up to 10.000e or multirange 2 x 3000e @ 0,3 µV/d in CE-M approved version for legal for trade use.
- Calibration, Set-Up parameters, configurable from keyboard or PC with Dinitools.
- Up to 8 signal linearization points with DINITOOLS (3 from keypad).
- Time Date.
- Memory back-up for recording dosage data in case it’s accidentally turned off.
- Printing the dosage and consumption data.
- From 12 Vdc to 24 Vdc power supply.
- EC Type Approval (EN45501)
- OIML R76
- OIML R61 - MID
- RS232/C bidirectional port configurable for connection with external units.
- RS485 bidirectional port configurable for network connection.
- Six 150 mA 48 Vac / 150 mA 60 Vdc (NO) photomosfet outputs configurables according to the selected dosage function.
- 2 configurable optoisolator photocoupler inputs: 12÷24 Vdc, 5 mA min - 20 mA max for START/STOP dosage.
- Analogue 16 bit output (only for DGTQFAN model), configurable as 4-20mA, 0-5Vdc or 0-10Vdc. Maximum load applicable on the output current: 350Ohm. Minimum load applicable on the output voltage: 10kOhm.
- Thermal printer for panel mounting
- Ethernet interface available using SETHIN unit
- 100-240 VAC 2,1 A 12 Vdc output, switching power adapter

Legal for trade approval

Printers/Labellers

Communication Interfaces

Connection cables

Power supply

Code	Description
ALSW	Built-in power supplier, with fixing bracket. 100-240 Vac 2,1 A input, 12 Vdc output.

Options for ATEX version

.

Detalii: