DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Interfata Cantar Profibus1s



Interfata Cantar Profibus1s. Producator: Dini Argeo.

Descriere

.

- Complete functionality from the Profibus-DP Slave, in according to IEC 61158.
- 32 input bytes / 32 bytes output.
- Automatic baud rate selection: from 9600 bit/s to 12Mbit/s.
- Available data: NET weight GROSS weight TARE weight Weight state/Error conditions DIGITAL INPUTS reading RELAY OUTPUT reading SETPOINT RELAY writing Alibi Memory SETUP configuration
- Complete functionality from the Profibus-DP Slave, in according to IEC 61158.
- 128 input bytes / 32 bytes output.
- Automatic baud rate selection: from 9600 bit/s to 12Mbit/s.
- Available data: NET weight GROSS weight Weight state/Error conditions
- ABS case for panel mounting on DIN bar.
- Dimensions lxwxh (mm): 120x111x22.5.
- Power supply: 12-24 Vdc.
- Max. consumption: 0,5A.
- RS485 interface on RJ485 connector for quick connection to DGT1S.
- Profibus port on 9 Pin connector.
- Board optoisolation against electric or electrostatic discharges.
- @DOWNLOAD

.

Detalii: