DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Platforma cantarire multifunctional cu solutie modulara



Platforma cantarire multifunctional cu solutie modulara. Producator: Dini Argeo.

Descriere

.

- DFWXP series weighing indicator: - Easy to clean ABS waterproof IP65 enclosure. - LCD backlit display with high contrast digits. - 5-key functional or 17-key numerical and functional waterproof keypad. - The "...PXP..." versions are fitted with attached thermal printer and real time clock. - Built-in rechargeable battery (60 hours with one 350-Ohm load cell) and 110-240 Vac internal power adapter.
- T series - single cell platform: - Steel tubular structure, oven-fire painted blue. - Satined AISI 304 stainless steel loading surface. - Adjustable resting feet and level.
- KEYBOARD: Zeroing, Automatic tare, Presettable tare, printing and/or data transmission, selectable function command, on/off switching. 17-key Version: Database of 10 tares, 2 Numeric IDs, keyboard lock, repetition of last printout made.
- SELECTABLE FUNCTIONS:
- High resolution visualization x 10, useful to view the weight with a sensitivity 10 times greater.
- Net/Gross conversion, it means the possibility to switch between the displaying of the net weight to the gross weight by pushing a button, when a tare is active.
- kg/lb conversion with the print of a receipt in both the two units.
- Horizontal accumulation: sum fo more successive weighs and print of the total.
- Formula weighing: manual mixing of various consecutive products according to the formula or loading of the pallet with various products and print of the total.
- +/- tolerance checking, to verify if the weight is within the desired limits.
- Percentage weighing, it means the displaying of the weight percentage on the scale compared with the configured 100%.
- Approved transmission of the weight to PC/PLC or data recording on MMC/USB (with Alibi memory ALMEM option).
- Simple pieces counting, with entry of the reference quantity or of the average unit weight with 17-key keyboard.
- Hold, manual freezing of the weight on display.
- Set Point Control (with DFIO option), on the net or gross weight, with programmable thresholds. When the threshold is reached, the correspondent relay is activated / deactivated.

- Printouts with customizable header.

Optional power supply cords

Weighing platforms

Code	l x w x h (mm)	Max (kg)	d (g)	d* HR (g)	CE-M* 3000e (g)	CE-M* 2x3000e (g)
TT6	330x330x93	6	1	0,2	2	1-2
TT15	330x330x93	15	2	0,5	5	2-5
TT30	330x330x93	30	5	1	10	5-10
TQ30	400x400x110	30	5	1	10	5-10
TQ60	400x400x110	60	10	2	20	10-20
TQ150	400x400x110	150	20	5	50	20-50
TX60	600x600x132	60	10	2	20	10-20
TX150	600x600x132	150	20	5	50	20-50
TX300	600x600x132	300	50	10	100	50-100

(*) These divisions are obtainable only with the relative options

Legal for trade approval

High resolution (d HR)(only at time of order)

Code	Description
THR	High Resolution (HR) model.

Storing the weighs (only at time of order)

Date&Time option

Communication Interfaces

Connection cables

Junction Box / Boards - Cell cables

Printers/Labellers

Attached control light box

Remote control

Columns and supports brackets

.

Detalii: