DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Platform cantarire multifunctionale din otel inoxidabil.



Platform cantarire multifunctionale din otel inoxidabil. Producator: Dini Argeo.

Descriere

.

- DFWKXT series weighing indicator: - Easy to clean STAINLESS STEEL waterproof IP68 enclosure. - LCD backlit display with high contrast digits. - 17-key numerical and functional waterproof keypad. - Built-in rechargeable battery (60 hours with one 350-Ohm load cell) and 110-240 Vac internal power adapter.
- TE series - single cell platform: - Structure with tubulars, mechanics, trinkets and satined steel loading surface in AISI304 stainless steel. - Adjustable feet and level.
- KEYBOARD: Zeroing, Automatic tare, Presettable tare, printing and/or data transmission, selectable function command, on/off switching, database of 10 tares, 2 Numeric IDs, keyboard lock, repetition of last printout made.
- SELECTABLE FUNCTIONS:
- High resolution visualization x 10, useful to view the weight with a sensitivity 10 times greater.
- Net/Gross conversion, it means the possibility to switch between the displaying of the net weight to the gross weight by pushing a button, when a tare is active.
- kg/lb conversion with the print of a receipt in both the two units.
- Horizontal accumulation: sum fo more successive weighs and print of the total.
- Formula weighing: manual mixing of various consecutive products according to the formula or loading of the pallet with various products and print of the total.
- +/- tolerance checking, to verify if the weight is within the desired limits.
- Percentage weighing, it means the displaying of the weight percentage on the scale compared with the configured 100%.
- Approved transmission of the weight to PC/PLC or data recording on MMC/USB (with Alibi memory ALMEM option).
- Simple pieces counting, with entry of the reference quantity or of the average unit weight.
- Hold, manual freezing of the weight on display.
- Set Point Control (with DFIO option), on the net or gross weight, with programmable thresholds. When the threshold is reached, the correspondent relay is activated / deactivated.
- Printouts with customizable header.

Optional power supply cords

Weighing platforms

Code	l x w x h (mm)	Max (kg)	d (g)	CE-M* 3000e (g)	CE-M* 2x3000e (g)	d* HR (g)
TTE6	330x330x93	6	1	2	1-2	0,5
TTE15	330x330x93	15	2	5	2-5	1
TTE30	330x330x93	30	5	10	5-10	2
TQE30	400x400x110	30	5	10	5-10	2
TQE60	400x400x110	60	10	20	10-20	5
TQE150	400x400x110	150	20	50	20-50	10
TXE60	600x600x132	60	10	20	10-20	5
TXE150	600x600x132	150	20	50	20-50	10
TXE300	600x600x132	300	50	100	50-100	20

(*) These divisions are obtainable only with the relative options

Legal for trade approval

High resolution (d HR)(only at time of order)

Code	Description
EHR	High resolution model for internal factory use.

Storing the weighs (only at time of order)

Printers/Labellers

Date&Time option

Attached control light box

Communication Interfaces

Remote control

Connection cables

Junction Box / Boards - Cell cables

Columns, supports brackets, visors

Charts for mobile weighing applications

Raising Frame

.

Detalii: