DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Bariera Zenner PW200XRD



Bariera Zenner PW200XRD, furnizorul de energie pt. Atex 1 si Zona 21. Producator : Dini Argeo.

Descriere

.

- Extremely versatile, and able to transform dangerous voltages coming from safe areas (24Vdc and 24/115/230Vac) into an intrinsic safety voltage, for powering devices in hazardous areas.
- Through the PW200IO option (4 intrinsically safe inputs and 4 intrinsically safe or 4 unprotected data outputs), the PW200XRD module allows to receive the signals from outside and to manage intrinsically safe devices or devices with greater absorption, such as relays, placed in the Exd box (for use with DFWATEXIO).
- Designed and made according to the ATEX94/9/CE directive, following the EN60079-0/60079-11/60079-31 norms.
- Exd case in aluminum alloy, with II 2GD Ex d IIC Ex tD A21 IP66 protection mode.
- The power supply voltages of the PW200XR models are: - 230 Vac (mod. PW200XRD - 230) - 115 Vac (mod. PW200XRD - 115) - 24 Vac (mod. PW200XRD - 24A) - 24 Vdc (mod. PW200XRD - 24D)
- Features of the intrinsically safe power supply output: - Vmax: 10,5 Vdc - Imax: 140 mA - Uo: 12,6 Vdc - Io: 340 mA - Lo: 700 µH - Co: 6,8 µF
- Equipped with a connection cable between PW200XRDxxx and DFWATEX2GDxxx, 1m long.
- 4 data inputs (Exi inputs), with the following features (for interfacing with DFWATEXIO indicator): - Ui: 40 Vdc - Ii: 30 mA - Li: 0 µH - Ci: 0 µF
- 4 intrinsically safe or unprotected data outputs (Exi inputs), with the following features (commanded by the DFWATEXIO indicator): INTRINSIC SAFETY:- Ui: 40 Vdc- Ii: 30 mA- Li: 0 µH- Ci: 0 µFNote: If these inputs and outputs are powered through an intrinsic safety voltage inside the PW200XRD, the overall max. absorbable current from the 4 outputs and 4 inputs is 40mA; so, if just 1 output is used, it can supply up to 20mA UNPROTECTED:- Umax: 48 Vac o 60Vdc- Imax: 150 mA

Accessories

.

Detalii: