DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Bariera Zenner KMB4



Bariera Zenner KMB4, cutie cu baraje pasive zenner de siguranta ,pt. medii atex. Producator: Dini Argeo.

Descriere

.

- Barrier for signal and sense: Fuse: 50mA Uo: 8.7V Io: 25mA Po: 0,05W Co: 5,9µF Lo: 56,88mH L/R: 662µH/Ohm Rmin: 352,8Ohm
- Barrier for supply: Fuse: 100mA Uo: 12V Io: 164mA Po: 0,49W Co: 1,41µF Lo: 1,32mH L/R: 72µH/Ohm Rmin: 73,5Ohm
- NOTE: connection with up to 4 load cells of 350 ohm each. WARNINGThe KMB4 kit can be placed in ATEX zone according to its ATEX marking or in alternative in a safe area. The electric coordination, executed for realizing the DCATEXMB4 certificate, involves the use of the LCCB cable, maximum length of 50m (greater lengths upon price estimate).

DFWATEX3GD Dini Argeo indicator and KMB4 box in ATEX 2 area, connected to the Dini Argeo ATEX platform in ATEX 1 & 21 areas. The system is provided with declaration of ATEX conformity (code DCATEXMB4).

Available versions:

Options only available at time of order:

.

Detalii: