DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Platforma cantarire profile -colaci tabla SW



Platforma cantarire SW, platforme de cantarire. Producator : Dini Argeo.

Descriere

.

- Functions with 1approved load cell protected against dust and water splashes according to IP65 standards and with OIML certification (350 Ohm input resistance).
- Sturdy painted steel section structure, and load surface with support bars, fixed edges, and flip-down edges on the operator side.
- Levers, cutters and bearings are in hardened ground chrome steel.
- Platform oscillation on steel balls and oscillation locks for avoiding overturns.
- Level.
- Up to 15 Vdc power supply
- IP67 hermetic junction box and wiring with 5m long 6-pin cable with connectors for connection to the indicator.
- Connection to the indicator and calibration with CE-M 3000e single range or 3000e+3000e dual range approval (depending on the indicators used).
- Models with special sizes and capacities (ask for estimate).

Available versions

Code	l x w x h (mm)	Max (kg)	d (g)	CE-M* 3000e (g)	CE-M* 2x3000e (g)
SWA15	1000x2000x650	1500	200	500	200-500
SWA30	1000x2000x650	3000	500	1000	500-1000
SWB15	1500x2000x650	1500	200	500	200-500
SWB30	1500x2000x650	3000	500	1000	500-1000
SWC15	1000x3000x650	1500	200	500	200-500
SWC30	1000x3000x650	3000	500	1000	500-1000
SWC60	1000x3000x650	6000	1000	2000	1000-2000
SWD30	1500x3000x650	3000	500	1000	500-1000
SWD60	1500x3000x650	6000	1000	2000	1000-2000

(*) These divisions are obtainable only with the relative options

Code	Description
DINICAL2	Calibration from 31 to 1500kg with Dini Argeo indicator. NET PRICE.
DINICAL3	Calibration from 1501 to 6000kg with Dini Argeo indicator. NET PRICE.

Legal for trade approval , class III or IIII, with Dini Argeo indicator (only at time of order)

Extractable extensions

Code	Description
BR3K	Extractable extensions l= 50 cm per side, for iron-weighing scales with capacities from 1500 to 3000 kg.
BR6K	Extractable extensions l= 50 cm per side, for iron-weighing scales with 6000 kg capacity.

Protection for junction box/electronic circuits

Calibration service with Dini Argeo indicator (only at time of order)

.

celula de cantarire cu protectie IP65

- structura din otel vopsit, cu bare de sprijin
- protectie impotriva rasturnarii
- bula de nivel
- cutie de jonctiuni IP67
- cablu pentru conectarea la indicator - 5m

Detalii: