DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Platforma cantarire CW



Platforma cantarire CW, inox. Producator: Dini Argeo.

Descriere

.

- Functions with a stainless steel, single point, approved load cell made according to OIML R60 standards, with protection against dust and moisture according to IP66 standards (350 Ohm input resistance).
- Bearing structure which may be fixed to the wall fitted with a quarter-weighing hook.
- Folding stainless steel loading surface, fitted with a fall-prevention safety piston.
- Up to 15 Vdc power supply.
- Shielded 3m long 6-pin cable with connectors for connection to the weight indicator.
- Connection to the indicator and calibration with CE-M 3000e single range or 3000e+3000e dual range approval (depending on the indicators used).
- Models with special sizes and capacities (ask for estimate).

Available versions

Code	l x w x h (mm)	Max (kg)	d (g)	CE-M* 3000e (g)	CE-M* 2x3000e (g)
CW12I15	490x500x1534	150	50	50	20-50
CW12I30	490x500x1534	300	100	100	50-100

(*) These divisions are obtainable only with the relative options

Code	Description
DINICAL2	Calibration from 31 to 1500kg with Dini Argeo indicator. NET PRICE.

Legal for trade approval , class III or IIII, with Dini Argeo indicator (only at time of order)

Calibration service with Dini Argeo indicator (only at time of order)

.

Detalii: