**DATA SPEED S.R.L.**
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

# Bara BLT



Bara BLT. Producator: Dini Argeo.

## Descriere

.

- Functions with 1 aluminium off-center load cell made according to OIML R60 standards, with protection against dust and water splashes according to IP67 standards (350 Ohm input resistance).
- It is made up of carbon steel oven-fire painted sections and tubulars and fitted with clamps for the installation.
- Up to 15 Vdc power supply.
- IP67 hermetic junction box with shielded 5m long 6-pin cable for connection to the indicator / flow integrator.
- To select the most suitable bar and verify in real time the feasibility of the system, fill in the data request form, which may be downloaded in the partners area.
- This data request form, correctly filled in, must accompany the price estimate request for the desired bar.
- Belt speed encoder.
- Calibration weight.
- Special sizes and capacities.
- CPWEBELT flow integrator.

Available versions

| Code | Belt w (mm) | Max (kg) | d (g) |
|---|---|---|---|
| BLT400 | 400 | 10 / 20 | 2 / 5 |
| BLT500 | 500 | 30 / 50 | 5 / 10 |
| BLT650 | 650 | 50 / 100 | 10 / 20 |
| BLT800 | 800 | 50 / 100 | 10 / 20 |
| BLT1000 | 1000 | 50 / 100 | 10 / 20 |
| BLT1200 | 1200 | 50 / 100 | 10 / 20 |

(*) The hourly flows shown on the chart are only approximate and are calculated assuming a belt speed of 40 m/min. and a material net weight on the weighed section equal to about a third of the load cell capacity

| Code | Description |
|---|---|
| TRV | Speed encoder fitted with fastening joint. |

Calibration weight

| Code | Description |
|---|---|
| PCAL | Calibration weight for bar for continuous weighing BLT series. |

Protection for junction box/electronic circuits

Calibration service with Dini Argeo indicator (only at time of order)

.

## Detalii: