DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Infinea Tab



Infinea Tab este un cititor de coduri de bare dedicat iPad. Permite citirea direct de pe tableta a codurilor de bare 1D/2D si comunica cu echipamente Datecs prin Bluetooth.

Descriere

SPECIFICATII TEHNICE

- Moduri de operare • Activ (turn on Infinea TAB) / Activ cu Scanare / Stand by (dupa 5 sec) • Activ (BT deconectat) / Active (BT conectat) / Cautare Activa • Cititor de carduri magnetice, Cititor de coduri de bare, Cititor RFID
- Baterie • incarcare de la USB sau Gang Charger • 1D: Peste 14,000 scanari si swipes per incarcare • 2D: Peste 8,000 scanari si swipes per incarcare
- Consum Bluetooth • BT in mod deconectat - 2,7 mA • BT in mod conectat - 22 mA • BT in mod cautare (search) - 42 mA
- Consum cititor coduri de bare • Cu scanare activata: 1D Engine – 110mA; 2D Engine - 230mA; Code 2D Engine - 350 mA • Mod Sleep - less than 1mA • Mod Deep Sleep - 12,8 µA (cu/fara iPad)
- Comunicare Bluetooth Communication (optional) • BT 2.0 Class 2 • Distanta - pana la 10 m • Serial Port Profile
- Cititor de coduri de bare (optional) • 1D Barcode Scanner: MDL-1000 Laser Scanning Engine • 2D Barcode Scanner: MDI-2300 Auto-focus Imager Scan Engine / CR-8000 Auto-focus Imager Scan Engine (Dual Optical Field)
- Coduri de bare compatibile: UCC/EAN 128, EAN 13, UPC A, Code 128, Code 39, Industrial 2of5, Micro QR code, QR code, RSS-Expanded, EAN 8, UPC E, GS1 RSS 14, Interleaved 2of5, DataMatrix, PDF417, MSI/Plessey, ISBN, IATA, Code 93, Codebar, S-code, RSS Limited, Maxi Code, UK/Plessey ISSN, ISMN, Code 11, Telepen, Matrix 2of5, MicroPDF417, Aztec
- Cititor de carduri RFID (optional): MiFARE Mini, ISO / IEC 14 443, MiFARE Classic 1K/4K, ISO / IEC 15 693, MiFARE Ultralight / Ultralight-C, DESFire, MiFARE Plus 2K / 4K, FeliCa
- Interfete: USB, RS232, Master/Slave Bluetooth RFCOMM , External RS (optional)
- W x L x H - 51 x 128 x 26 mm
- Greutate - 105 g
- Alimentare: External 5V / Internal Baterie Li-ion 3.7V/1100mAh
- Temperatura de functionare: de la 0 C la 40 C
- Temperatura depozitare: de la -5 C la 40 C