DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Posiflex XT3215



Posiflex XT-3215 Pe piata Horeca si retail terminalul POS nu mai este doar o unealta de business. E o parte decorativa a magazinului, o parte din imaginea acestuia. Fiecare curba si detaliu al terminalului POS ar trebui sa adauge o stare de spirit magazinului.

Descriere

Specificatiile Produsului

Processor: Intel D525 / 1.8GHz / 1M Cache (dual core)
System Memory: DDR3 800MHz SO-DIMM x 1, factory default 2GB
Storage Device: SATA Storage x 2, factory default 320GB-HDD x 1
Power Supply: 12V / 60W
OS: POSReady 7
Display & Touch
LCD Display: 15" TFT LCD 1024 x 768
Touch Function: Resistive Touch
I/O & Expansion
Serial Port: 4, DB9 x 3 + RJ45 x 1, 5V / 12V support on all COM ports
Parallel Port: 1, via optional conversion cable
Standard USB Port: 5
Powered USB: Optional 24V x 1 + 12V x 2 via 8th generation base
LAN Port: 10 / 100 / 1000 Mb x 2
VGA Port: VGA x 1, 12V support for Posiflex monitors
CR Port: 1, control 2 CR via optional Y-cable
UPS Port: Yes
Extension Slot: mini-PCIe slot x 1
Built-in Device
Built-in WIFI: Optional mini-PCIe WIFI module