DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Cantare de verificare compact SXS



Cantare de verificare compact SXS Producator : Kern

Descriere

- Ideal for the robust industry
- Robust stainless steel display device with IP68 protection, ideal for industrial applications, for easy and hygienic cleaning, with integrated power supply. Wall mount standard. Details: KERN KXS-TM
- Superior display size: digit height 55 mm. Bright backlight for easy reading of weight, even in poor lighting conditions
- Stainless steel weighing plate
- Substructure in wing design, extremely resistant to bending, steel, lacquered
- Load cells aluminium, silicone-coated. IP65: Protected against dust and water splashes
- ESD drain to protect against electrostatic discharge e. g. for electrostatically-charged items to be weighed or people who work with the balance
- Thanks to the RS-232, RS 485 and Bluetooth (optional) interfaces, the balance can easily be connected to existing networks. Data exchange between the balance and PC or printer is also made easier

Ideal pentru industria robust

Dispozitiv robust din oțel inoxidabil de afișare cu protecție IP68, ideale pentru aplicații industriale, pentru curățare ușoară și igienică, cu sursa de alimentare integrată. Montare pe perete standard. Detalii: KERN KXS-TM

Superior dimensiune de afișare: înălțime cifre 55 mm. Iluminare de fundal luminos pentru o citire ușoară de greutate, chiar și în condiții de iluminare slabă

Placă de cântărire din oțel inoxidabil

Strat suport în proiectarea aripa, extrem de rezistent la îndoire, oțel, lăcuit

Încărcați celule aluminiu, acoperite cu silicon. IP65: Protecție împotriva prafului și stropi de apă

Scurgere ESD pentru a proteja împotriva descărcărilor electrostatice e. g. pentru elemente care trebuie cântărite sau persoane care lucreaza cu echilibrul electrostatic, încărcat

Datorită RS-232, RS 485 și (opțional) interfețe Bluetooth, soldul poate fi usor conectat la rețelele existente. Schimbul de date între balanța și PC-ul sau imprimanta este, de asemenea, face mai ușor

Item number	Weighing range [Max] kg	Readout [d] g	Verification value [e] g	Minimum load [Min] g

SXS 6K-3M	3 | 6	1 | 2	1 | 2	20 | 40
SXS 10K-3M	6 | 15	2 | 5	2 | 5	40 | 100
SXS 10K-3LM	6 | 15	2 | 5	2 | 5	40 | 100
SXS 30K-2M	15 | 30	5 | 10	5 | 10	100 | 200
SXS 30K-2LM	15 | 30	5 | 10	5 | 10	100 | 200
SXS 60K-2M	30 | 60	10 | 20	10 | 20	200 | 400
SXS 60K-2LM	30 | 60	10 | 20	10 | 20	200 | 400
SXS 100K-2M	60 | 150	20 | 50	20 | 50	400 | 1000
SXS 100K-2LM	60 | 150	20 | 50	20 | 50	400 | 1000
SXS 300K-2M	150 | 300	50 | 100	50 | 100	1000 | 2000