DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Indicator cantarire DFWLAP



Indicator cantarire DFWLAP. Producator: Dini Argeo.

Descriere

- 5-key waterproof keypad.
- Backlit 25 mm LCD display with 6 high contrast digits with icons for showing the active functions.
- Easy to clean, IP67 ABS waterproof case, resistant to corrosive environments.
- Dimensions: 230 x 54 x 165 mm.
- A/D 24 bit, 4 channels converter, max. 200 conv./sec. autoselect, and up to 8 signal linearisation points.
- Up to 10.000e (also multirange 3 x 3000e in the DFWLAP version) @ 0,3 µV/d in CE-M approved version for legal for trade use.
- Up to 1.000.000 displayable divisions with internal resolution up to 3.000.000 points.
- Digital calibration and Set-Up from keypad or from PC through DINITOOLS.
- Connection with up to 8 load cells with input resistance equal to 350 Ohm or up to 16 cells of 700 Ohm each. 4 analogue reading channels.
- Power supply through built-in rechargeable battery, with about 40-hour operating time depending on the using mode.
- Fitted with battery charger.
- Digital equalisation of the 4 reading channels, with visualization of the total weight.
- KEYBOARD FUNCTIONS: Zeroing, Tara, Transmission of the displayed weight to PC or Print function on repeater, Selectable function command which can be: x10 Visualization, Net/Gross or lb/kg Conversion, Weight totalisation, Formulation, +/- Check, % weighing, Approved transmission of the weight to PC/PLC (with Alibi memory ALMEM option), Counting, Input/Output, Hold, Peak.
- Independent calibration of the 4 channels, with transmission of each weigh and of the sum to the PC or DFWKRPRF repeater.
- FUNCTIONS WITH DFWKRPRF: Zeroing, Tare, Wheel/axle weighing, Input/output weighing, Tractor + Trailer Totalisation, Centre of gravity calculation, Display and Printing on DFWKRPRF of the single channel/Channel combinations/Weight total/Input-output difference/Vehicles' total/Centre of gravity coordinates.

Code	Description

DFWLAP-1	Wireless weight transmitter for connection to the main indicator or PC. Max. functioning distance, in appropriate environmental and installation conditions: 70m indoors, 150m outdoors. 50 configurable channels. Fitted with standard weighing program with digital equalisation of 4 reading channels.
DFWLAPKR-1	Wireless weight transmitter for connection to the DFWKRPRF weight repeater or PC, ideal to create weighing station without cable. Max. functioning distance, in appropriate environmental and installation conditions: 70m indoors, 150m outdoors. 50 configurable channels. Fitted with static wheel weighing / axle weighing programme.

WIRELESS VEHICLES WEIGHING SYSTEMS WITH VARIOUS INDEPENDENT PLATFORMS

WEIGH BRIDGES, PLATFORMS, WEIGHING SYSTEMS WITH 1 OR MORE EQUALISED LOAD CELLS (DIGITALLY OR THROUGH JUNCTION BOX)

CARACTERISTICI TEHNICE

Tastatura rezistenta la apa 5-cheie.

Backlit 25 mm Afișaj LCD cu 6 cifre contrast înalt cu icoane pentru care prezintă funcțiile activi.

Ușor de curățat, IP67 ABS caz impermeabil, rezistent la medii corozive.

Dimensiuni: 230 x 54 x 165 mm.

A / D de 24 biti, 4 canale Convertor, max. 200 conv. / Sec. AutoSelect, și până la 8 puncte de liniarizare a semnalului.

Până la 10.000e (de asemenea, multirange 3 x 3000e în versiunea DFWLAP) @ 0,3 µV / d în CE-M aprobat versiunea pentru legală pentru utilizarea comercială.

Până la 1.000.000 diviziuni afișabil cu rezoluție de până la 3.000.000 puncte interne.

Calibrare digitală și Set-Up de la tastatură sau de la PC prin DINITOOLS.

Conexiune cu până la 8 celule de sarcină cu o rezistență de intrare egală cu 350 Ohm sau până la 16 de celule de 700 Ohm fiecare. 4 canale de citire analog.

Sursa de alimentare prin intermediul built-in baterie reîncărcabilă, cu durată mare de funcționare aproximativ 40 de ore, în funcție de modul de utilizarea.

Echipat cu încărcător de baterie.

DFWLAP: cutie egalizare Wireless

Egalizare digitală a 4 canale de citire, cu vizualizare din greutatea totală.

Funcții ale tastaturii: Zero, Tara, Transmisie din greutatea afișată la PC sau Print funcție pe repetor, funcție selectată, care poate fi: x10 vizualizare, net / brut sau lb / kg de conversie, Greutate totalizare, formulare, +/- Cec,% de cântărire, de transmisie și aprobată de greutate la PC / PLC (cu Alibi opțiune ALMEM memorie), de numărare, de intrare / ieșire, Hold, Peak.

DFWLAPKR: Multi Balanta transmițător (până la 4)

Calibrare independent de 4 canale, cu transmisie de fiecare cântărește și a sumei la PC sau DFWKRPRF repetor.

FUNCȚII CU DFWKRPRF: Zero, proprie, roata / osie de cântărire, de intrare / ieșire de cântărire, Tractor + Trailer totalizare, Centrul de calcul greutate, Display și Imprimare pe DFWKRPRF de combinațiile singur canal / canal / greutate totală / diferență de intrare-ieșire / Vehicule "totală / Centrul de greutate coordonate.