DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Balanta analitica GAT



Balanta analitica GAT. Producator: Dini Argeo. Divizia:0,0001g. Capacitate: 120g,220g.

Descriere

- Backlit LCD display with 8 digits.
- Waterproof membrane keypad, with 7 keys.
- Construction: bearing structure in die cast aluminium, ABS case.
- Weight detection through tuning fork system.
- Stainless steel plate, size: Ø 80mm.
- Windscreen, level, and adjustable feet.
- Power supply: standard fitted with 230 Vac power adapter.
- RS232/c port for connection to PC, 3590E series indicator or printer.
- DIN8P port for connection to external devices.
- Internal calibration.
- Upon request: - ACCREDIA calibration with issuing of relative certificate; - CE-M approval; - weigh-below hook.
- counting;
- % weight;
- conversion units of measure: mg, ct, oz, lb, ozt, dwt;
- accumulation;
- zeroing;
- zero tracking;
- semi-automatic tare;
- digital calibration.

(*) CE-M divisions are obtainable only with the relative options.

Code	Description
ECEM1L	CE-M approval for class I or II scales with capacity up to 6kg.
OBTPRSH	ABS thermal printer for Scale House products (to be combined with specific cable for each scale). 58 mm paper width; 50 mm roll diameter; power supply through built-in 110-240 Vac power adapter.
RSCBSHTP	1,5 m cable for connecting ALD and NPS series scales to OBTPRSH printer.
RSCBP2P	1,5m cable for connecting to PC.

RSCBSHEG	(S1) RS232 cable for 3590EGT connection.

CARACTERISTICI TEHNICE

Ecran LCD cu iluminare din spate cu 8 cifre.

Tastatura cu membrană impermeabilă, cu 7 taste.

Construcție: având structura din aluminiu turnat, caz ABS.

Detectare greutate prin sistemul diapazon.

Placă de oțel inoxidabil, dimensiune: Ø 80mm.

Parbriz, nivel, și picioare reglabile.

Sursa de alimentare: standard, dotate cu 230 adaptor de alimentare Vac.

RS232 / Port C pentru conectarea la PC, indicator seria 3590E sau imprimanta.

Port DIN8P pentru conectarea la dispozitive externe.

Calibrare internă.

la cerere:

- ACCREDIA calibrare cu eliberarea certificatului de relativă;
- Omologare CE-M;
- Cântărește-jos cârlig.

FUNCȚII

numărare;

% În greutate;

unități de conversie de măsură: mg, ct, oz, lb, ozt, dwt;

acumulare;

reducerea la zero;

urmărire zero;

tare semi-automate;

calibrare digitală.