DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Balanta de precizie GAI



Balanta de precizie GAI. Producator: Dini Argeo Capacitate;420g,620g,2200g,4200g. Diviziune: 0.01g,0.001g.

Descriere

- Backlit LCD display with 7 digits 16.5mm high.
- Waterproof membrane keypad, with 5 keys.
- Construction: bearing structure in die cast aluminium, ABS case.
- Weight detection through tuning fork system.
- Stainless steel plate, size: - GAI420 and GAI620 models Ø 118mm - GAI2200 and GAI4200 models 180x160mm.
- Draught shield (on GAI420 and GAI620 models), level, adjustable feet.
- Power supply: standard fitte with 230 Vac power adapter.
- RS232/c port for connection to PC, 3590E series indicator or printer.
- Internal calibration.
- Upon request: - ACCREDIA calibration with issuing of relative certificate; - CE-M approval; - weigh-below hook.
- counting;
- % weight;
- conversion units of measure: - Standard versions, not approved: g, kg, ct, oz, lb, ozt, dwt; - CM versions, approved: g, kg, ct (only available at time of scale's order);
- zeroing;
- zero tracking;
- semi-automatic tare;
- digital calibration.

(*) CE-M divisions are obtainable only with the relative options.

Code	Description
ECEM1L	CE-M approval for class I or II scales with capacity up to 6kg.
OBTPRSH	ABS thermal printer for Scale House products (to be combined with specific cable for each scale). 58 mm paper width; 50 mm roll diameter; power supply through built-in 110-240 Vac power adapter.
RSCBSHTP	1,5 m cable for connecting ALD and NPS series scales to OBTPRSH printer.

RSCBP2P	1,5m cable for connecting to PC.
RSCBSHEG	(S1) RS232 cable for 3590EGT connection.

CARACTERISTICI TEHNICE

Ecran LCD cu iluminare din spate cu 7 cifre 16.5mm mare.

Tastatura cu membrană impermeabilă, cu 5 taste.

Construcție: având structura din aluminiu turnat, caz ABS.

Detectare greutate prin sistemul diapazon.

Placă de oțel inoxidabil, dimensiune:

- Modele GAI420 și GAI620 Ø 118mm
- GAI2200 și GAI4200 modele 180x160mm.

Scut pescaj (pe GAI420 și modele GAI620), nivel, picioare reglabile.

Sursa de alimentare: Fitte standard de 230 adaptor de alimentare Vac.

RS232 / Port C pentru conectarea la PC, indicator seria 3590E sau imprimanta.

Calibrare internă.

la cerere:

- ACCREDIA calibrare cu eliberarea certificatului de relativă;
- Omologare CE-M;
- Cântărește-jos cârlig.

FUNCȚII

numărare;

% În greutate;

unități de conversie de măsură:

- Versiuni standard, nu au fost aprobate: g, kg, ct, oz, lb, ozt, dwt;
- Versiuni CM, aprobat: g, kg, ct (disponibil numai la momentul comenzii scară lui);

reducerea la zero;

urmărire zero;

tare semi-automate;

calibrare digitală.