DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Balanta de precizie HLD 150-600g



Balanta de precizie HLD 150-600g. Producator: Dini Argeo. Divizie: 0.002g,0.01g. Capacitate:150g,300g,600g.

Descriere

- Backlit LCD display with 7 digits 16mm high.
- Waterproof membrane keypad, with acoustic feedback, with 7 keys.
- Stainless steel plate, size: - HLD150 model Ø 80mm - HLD300 and HLD600 models Ø 120mm.Draught shield, level and adjustable feet.
- Built-in rechargeable battery (about 30h battery life) and 230 Vac power adapter.
- RS232/c port for connection to PC or printer.
- Packaging: 370x240x250mm size - approximate weight of 2,7kg.
- Upon request: - ACCREDIA calibration with issuing of relative certificate - CE-M approval.
- counting;
- % weight;
- weight totalisation;
- conversion up to 13 units of measure;
- zeroing;
- zero tracking;
- semi-automatic tare;
- digital calibration;
- backlight command;
- low battery warning.
- Internal sensitivity and minimum recommended A.P.W.:

0,0004

0,0005

0,001

0,002

0,005

0,01

(*) CE-M divisions are obtainable only with the relative options.

Code	Description
ECEM1L	CE-M approval for class I or II scales with capacity up to 6kg.
OBTPRSH	ABS thermal printer for Scale House products (to be combined with specific cable for each scale). 58 mm paper width; 50 mm roll diameter; power supply through built-in 110-240 Vac power adapter.
RSCBBC	1,5 m cable for connecting AFW, ALGM, ASB, ASC, ASG, BCSD and HLD series scales to OBTPRSH printer.
RSCBPCBC	1,5 m cable for connecting AFW, ALGM, ASC, BCSD, HLD and KS series scales to PC.

CARACTERISTICI TEHNICE

Ecran LCD cu iluminare din spate cu 7 cifre 16mm înalt.

Tastatura impermeabil cu membrană, cu feedback-ul acustic, cu 7 taste.

Placă de oțel inoxidabil, dimensiune:

- HLD150 modelul Ø 80mm
- Modele HLD300 și HLD600 Ø 120mm.Draught scut, nivel și picioare reglabile.

Built-in baterie reîncărcabilă (despre viața bateriei 30h) și 230 adaptor de alimentare Vac.

RS232 port / C pentru conectarea la PC sau imprimanta.

Ambalaj: dimensiunea 370x240x250mm - greutate aproximativă de 2,7kg.

la cerere:

- ACCREDIA calibrare cu eliberarea certificatului de relativă
- Omologare CE-M.

FUNCȚII

numărare;

% În greutate;

greutate de totalizare;

conversie de până la 13 de unități de măsură;

reducerea la zero;

urmărire zero;

tare semi-automate;

calibrare digitală;

comandă lumina de fundal;

avertizare baterie descărcată.

numărarea caracteristicilor

Sensibilitate internă și minim recomandat APW:

Model de HLD150 HLD300 HLD600

Sensibilitate intern g 0,0004

0,0005

0,001

Min. recomandată A.P.W. g 0,002

0,005

0,01