DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Balanta de precizie ALD 2100g-4100g



Balanta de precizie ALD 2100g-4100g. Producator: Dini Argeo. Division:0.01g. CApacitate: 2100g.

Descriere

- Backlit LCD display with 7 numeric digits 15mm high and 10 alphanumeric characters 7mm high.
- Waterproof membrane keypad, with 4 keys.
- Construction: bearing structure in die cast aluminium, ABS case.
- Weight detection through electromagnetic monobloc compensation load cell.
- Stainless steel plate, size 195x200mm.
- Level and adjustable feet.
- Weight-below hook.
- Power supply: 100-240 Vac 50Hz – 12 Vdc mains power adapter.
- RS232/c port interface for connection to PC, 3590E series indicator or printer.
- Packing: 390x500x340mm size – approximate weight of 4,9kg.
- Upon request: - ACCREDIA calibration with issuing of relative certificate; - CE-M approval; - bracket for safety hook.
- counting;
- % weight;
- conversion units of measure: - Standard versions, not approved: mg, g, kg, ct, lb, oz; - CM versions, approved: g, kg, ct (only available at time of scale's order);
- zeroing;
- zero tracking;
- semi-automatic tare;
- digital calibration;
- low battery warning.
- Internal sensitivity and minimum recommended A.P.W.:

< 0,005

0,01

(*) CE-M divisions are obtainable only with the relative options.

Code	Description
ECEM1L	CE-M approval for class I or II scales with capacity up to 6kg.
OBTPRSH	ABS thermal printer for Scale House products (to be combined with specific cable for each scale). 58 mm paper width; 50 mm roll diameter; power supply through built-in 110-240 Vac power adapter.

RSCBSHTP	1,5 m cable for connecting ALD and NPS series scales to OBTPRSH printer.
RSCBP2P	1,5m cable for connecting to PC.
RSCBSHE	1,5m cable for connecting to 3590E indicators.

CARACTERISTICI TEHNICE

Ecran LCD cu iluminare din spate cu 7 numeric 15mm cifre mari și 10 caractere alfanumerice 7mm mare.

Tastatura cu membrană impermeabilă, cu 4 taste.

Construcție: având structura din aluminiu turnat, caz ABS.

Detectare greutate prin monobloc electromagnetic de celule de sarcină de compensare.

Placă de oțel inoxidabil, dimensiune 195x200mm.

Nivel și picioare reglabile.

-Greutate de mai jos cârlig.

Sursa de alimentare: 100-240 Vac 50Hz - 12 Vdc Sursă de alimentare adaptor.

RS232 / C port pentru conectarea la PC, indicator seria 3590E sau imprimanta.

Ambalaj: dimensiunea 390x500x340mm - greutate aproximativă de 4,9kg.

la cerere:

- ACCREDIA calibrare cu eliberarea certificatului de relativă;
- Omologare CE-M;
- Suport pentru cârlig de siguranță.

FUNCȚII

numărare;

% În greutate;

unități de conversie de măsură:

- Versiuni standard, nu au fost aprobate: mg, g, kg, ct, lb, oz;
- Versiuni CM, aprobat: g, kg, ct (disponibil numai la momentul comenzii scară lui);

reducerea la zero;

urmărire zero;

tare semi-automate;

calibrare digitală;

avertizare baterie descărcată.

Numărarea caracteristicilor

Sensibilitate internă și minim recomandat APW:

Sensibilitate intern g

<0,005

Min. recomandată A.P.W. g 0,01