DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Analizor de umiditate ALGM



Analizor de umiditate ALGM. Producator: Dini Argeo. Divizie:0.001g. Capacitate:210g.

Descriere

- Graphic LCD display and waterproof membrane keypad.
- Selection of the programme language in the set-up.
- 2 halogen 200 W lamps.
- 10 sample plates.
- Resolution: 0,01%.
- Drying temperature: up to 160°C.
- Heating time (100°C): approximate time of 1 min.
- Drying time: up to 10h.
- Power supply: 230 Vac power adapter.
- PS2 input for connecting external PC keyboard.
- RS232/c port for connection to PC or printer.
- Upon request: - set of sample plates; - ACCREDIA calibration with issuing of the relative certificate.
- Drying modes: end when reaching the established time, automatic end.
- Calculation methods: % of dry weight, % of humidity in relation to initial weight or to dry weight.
- Memory for up to 10 customized programs (mode, temperature, time, calculation method).
- Calculation and printing of the statistical evaluations.
- Displays the drying graphs.
- Entering free texts and computing the report through external PC keyboard.
- Date and time.
- Digital calibration.
- Semi-automatic tare.

Code	Max (g)	d (g)
ALGM210	210	0,001

Code	Description
OBTPRSH	ABS thermal printer for Scale House products (to be combined with specific cable for each scale). 58 mm paper width; 50 mm roll diameter; power supply through built-in 110-240 Vac power adapter.
RSCBBC	1,5 m cable for connecting AFW, ALGM, ASB, ASC, ASG, BCSD and HLD series scales to OBTPRSH printer.
RSCBPCBC	1,5 m cable for connecting AFW, ALGM, ASC, BCSD, HLD and KS series scales to PC.

CARACTERISTICI TEHNICE

Ecran LCD grafic și rezistent la apa tastatura cu membrană.

Selectarea limbii programului în set-up.

2 halogen 200 W lampi.

10 plăci de probă.

Rezoluție: 0,01%.

Temperatura de uscare: până la 160 ° C.

Timp de încălzire (100 ° C): timp de aproximativ 1 min.

Timp de uscare: pana la 10h.

Sursa de alimentare: 230 Vac adaptorul de alimentare.

Intrare PS2 pentru conectarea tastaturii PC extern.

RS232 port / C pentru conectarea la PC sau imprimanta.

la cerere:

- Set de plăci de probă;
- Calibrare ACCREDIA cu eliberarea certificatului relative.

FUNCȚII

Uscarea moduri: sfârșitul atunci când ajunge la termenul stabilit, la sfârșitul automată.

Metode de calcul:% din greutatea uscată,% din umiditate în raport cu greutatea inițială sau să se usuce în greutate.

Memorie de până la 10 programe personalizate (modul, temperatura, timpul, metoda de calcul).

Calculul și tipărirea a evaluărilor statistice.

Afișează graficele de uscare.

Introducerea textelor libere și de calcul a raportului prin tastatura PC extern.

data si ora.

Calibrare Digital.

Tare semi-automat.