DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Cantar numarator NWL



Cantar numarator NWS. Producator: Dini Argeo.

Descriere

- Backlit LCD display with 6 digits 28mm high.
- Mechanical waterproof keypad with 8 keys and acoustic feedback.
- Stainless steel plate, 235x335mm size.
- Level and adjustable feet.
- Built-in rechargeable battery 4Vdc (about 100h battery life) and 230Vac power adapter.
- Packaging: 380x130x370mm size - approximate weight of 4kg.
- Master Pack: 2x(380x130x370)mm size - 2 x approximate weight of 4kg.
- Upon request: - ACCREDIA calibration with issuing of relative certificate;
- counting;
- % weight;
- weight check, with 2 thresholds and acoustic alarm;
- lb/kg conversion;
- weighing filter selection;
- zeroing;
- zero tracking;
- semi-automatic tare;
- digital calibration;
- backlight command;
- low battery warning.
- Internal sensitivity and minimum accepted A.P.W.:

0,02

0,05

0,1

0,1

1

2,5

5

0,5

Code	Max (kg)	d (g)	d HR (g)*
NWL6K	6	2	1
NWL15K	15	5	2
NWL30K	30	10	5
NWLH30K	30	1	-

(*) HR divisions programmable from set-up.

CARACTERISTICI TEHNICE

Ecran LCD cu iluminare din spate cu 6 cifre 28mm înalt.

Tastatura rezistenta la apa mecanic cu 8 taste și feedback-ul acustic.

Placă de oțel inoxidabil, dimensiune 235x335mm.

Nivel și picioare reglabile.

Built-in baterie reîncărcabilă 4Vdc (aproximativ 100h de viață a bateriei) și adaptor de alimentare 230Vac.

Ambalaj: dimensiunea 380x130x370mm - greutate aproximativă de 4 kg.

Maestrul Pack: 2x (380x130x370) mm dimensiuni - 2 x greutate aproximativă de 4 kg.

la cerere:

- ACCREDIA calibrare cu eliberarea certificatului de relativă;

FUNCȚII

numărare;

% În greutate;

verificare greutate, cu 2 praguri și de alarmă acustice;

lb conversie / kg;

cântărire de selecție filtru;

reducerea la zero;

urmărire zero;

tare semi-automate;

calibrare digitală;

comandă lumina de fundal;

avertizare baterie descărcată.

numărarea caracteristicilor

Sensibilitate internă și minim acceptat A.P.W .:

Model de NWL6K NWL15K NWL30K NWLH30K

Sensibilitate intern g 0,02

0,05

0,1

0,1

Min. acceptată A.P.W. g 1

2,5

5

0,5