DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Cantar numarator ASW



Cantar numarator ASW. Producator: Dini Argeo.

Descriere

- Backlit LCD display with 6 digits 24 mm high.
- Membrane waterproof keypad with 7 digits and acoustic feedback.
- Stainless steel plate, 230x300mm size.
- Adjustable feet and level.
- Built-in rechargeable battery (about 70h battery life) and 230 Vac power adapter.
- Packaging: 415x380x190mm size - approximate weight of 5kg.
- Master Pack: 2 x (415x380x190)mm size - 2 x approximate weight of 5kg.
- Upon request: ACCREDIA calibration with issuing of relative certificate.
- counting:
- % weight;
- weight, pieces or % quantity check, with 2 thresholds and acoustic alarm,
- weight totalisation;
- unit of measure conversion: kg, g, lb, oz;
- zeroing;
- zero tracking;
- semi-automatic tare;
- digital calibration;
- auto switch-off;
- backlight command;
- low battery warning.
- Internal sensitivity and minimum recommended A.P.W.:

0,01

0,1

0,05

0,5

Code	Max (kg)	d (g)
ASW3	3	0,1
ASW30	30	1

CARACTERISTICI TEHNICE
Ecran LCD cu iluminare din spate cu 6 cifre de 24 mm înălțime.
Tastatura cu membrană impermeabilă, cu 7 cifre și feedback-ul acustic.
Placă de oțel inoxidabil, dimensiune 230x300mm.
Picioare și la nivel reglabile.
Built-in baterie reîncărcabilă (despre viața bateriei 70h) și 230 adaptor de alimentare Vac.
Ambalaj: dimensiunea 415x380x190mm - greutate aproximativă de 5 kg.
Maestrul Pachet: 2 x (415x380x190) mm dimensiuni - 2 x greutate aproximativă de 5 kg.
La cerere: calibrare ACCREDIA cu eliberarea certificatului de relativă.
FUNCȚII
numărare:
% În greutate;
greutate, piese sau verificați cantitatea%, cu 2 praguri și sistemul de alarmă acustică, greutate de totalizare;
unitate de conversie de măsură: kg, g, lb, oz;
reducerea la zero;
urmărire zero;
tare semi-automate;
calibrare digitală;
oprire automată;
comandă lumina de fundal;
avertizare baterie descărcată.
numărarea caracteristicilor
Sensibilitate internă și minim recomandat APW:
Modelul ASW3 ASW30
Sensibilitate intern g 0,01
0,1
Min. recomandată A.P.W. g 0,05
0,5