DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Cantar numarator BCSD



Cantar numarator BCSD. Producator: Dini Argeo.

Descriere

- 3 backlit LCD displays with 6 digits 20mm high for simultaneously viewing weight, average piece weight, and number of pieces.
- Membrane waterproof, alphanumeric and functional keypad with 20 keys and acoustic feedback.
- Stainless steel plate, 230x300mm size.
- Level and adjustable feet.
- Built-in rechargeable battery (about 70h battery life) and 230Vac power adapter.
- RS232/C port for connection to PC or printer.
- Configurable input for connection to second counting platform, with completely programmable capacity and division.
- Packaging: 440x370x220mm size - approximate weight of 5,5kg.
- Master Pack: 2 x (440x370x220)mm size - 2 x approximate weight of 5,5kg.
- Upon request: ACCREDIA calibration with issuing of relative certificate.
- counting: - entry of sampling items, - entry of Average Piece Weight, - optimisation of the A.P.W., - indication of insufficient A.P.W./sampling quantity, - 100 PLU memory, each with: alphanumeric description of 12 characters, tare, A.P.W.;
- weight or piece quantity check, with 2 thresholds and acoustic alarm;
- weight and pieces' totalisation;
- unit of measure conversion: kg, lb;
- zeroing;
- zero tracking;
- semi-automatic tare or enterable from keypad;
- digital calibration;
- auto switch-off;
- backlight command;
- low battery warning.
- Internal sensitivity and minimum recommended A.P.W.:

0,02

0,05

0,1

0,1

0,2

0,5

Code	Max (kg)	d (g)
BCSD6	6	0,1
BCSD15	15	0,2
BCSD30	30	0,5

NOTE: available connection to a second remote platform of SCALE HOUSE series.

Code	Description
SHCAL1	Calibration service for platform up to 30 kg, connected to Scale House weight indicator - NET PRICE
SHCAL2	Calibration service for platform from 31 to 1500 kg, connected to Scale House weight indicator - NET PRICE
SHCAL3	Calibration service for platform from 1501 to 6000 kg, connected to Scale House weight indicator - NET PRICE
OBTPRSH	ABS thermal printer for Scale House products (to be combined with specific cable for each scale). 58 mm paper width; 50 mm roll diameter; power supply through built-in 110-240 Vac power adapter.
RSCBBC	1,5 m cable for connecting AFW, ALGM, ASB, ASC, ASG, BCSD and HLD series scales to OBTPRSH printer.
RSCBPCBC	1,5 m cable for connecting AFW, ALGM, ASC, BCSD, HLD and KS series scales to PC.

CARACTERISTICI TEHNICE

3 LCD cu iluminare din spate cu 6 cifre 20mm mare pentru greutatea vizualizarea simultan, greutatea medie bucată, și numărul de bucăți.

Membrană impermeabilă, alfanumerică și tastatură funcțională cu 20 taste și feedback-ul acustic.

Placă de oțel inoxidabil, dimensiune 230x300mm.

Nivel și picioare reglabile.

Built-in baterie reîncărcabilă (despre viața bateriei 70h) și adaptor de alimentare 230Vac.

Port RS232 / C pentru conectarea la PC sau imprimanta.

Intrare configurabil pentru conectarea a doua platforma de numărare, cu o capacitate complet programabile și diviziune.

Ambalaj: dimensiunea 440x370x220mm - greutate aproximativă de 5,5kg.

Maestrul Pachet: 2 x (440x370x220) mm dimensiuni - 2 x greutate aproximativă de 5,5kg.

La cerere: calibrare ACCREDIA cu eliberarea certificatului de relativă.

FUNCȚII

numărare:

- Intrare de articole de eșantionare,
- Intrare de piese Greutate medie,
- Optimizarea A.P.W.,
- Indicarea insuficiente APW cantitate / prelevare de probe,
- 100 memorie PLU, fiecare cu: descrierea alfanumeric de 12 caractere, tare, APW;

greutate sau piese de selectare cantitate, cu 2 praguri și de alarmă acustice;

greutate și de totalizare bucăți ";

unitate de conversie de măsură: kg, lb;

reducerea la zero;

urmărire zero;

semi-automat tară sau enterable la tastatura;

calibrare digitală;

oprire automată;

comandă lumina de fundal;

avertizare baterie descărcată.
Numărarea caracteristicilor
Sensibilitate internă și minim recomandat APW:
Model de BCSD6 BCSD15 BCSD30
Sensibilitate intern g 0,02
0,05
0,1
Min. recomandată A.P.W. g 0,1
0,2
0,5