DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

CO1-Antiv



CO1-Antiv. Producator: Sensocar.

Descriere

Capacity 300 – 500 – 750 – 1000 – 1500 kg 4000 divisions OIML-R60
Measuring element from steel alloy
Protected against corrosion by nickel-plated treatment
Available in stainless steel
Protected against humidity IP-67
Avalable in ATEX version (optional)
[II 1GD Ex ia IIC T4...T6 Ga]
[II 1GD Ex ia IIIC T135ºC Da]
Technical data
Capacitate 300-500 - 750-1000 - 1500 kg
4000 diviziuni OIML-R60
Element de măsură din aliaj de oțel
Protejate împotriva coroziunii prin tratarea placat cu nichel
Disponibil din oțel inoxidabil
Protejat împotriva umidității IP-67
Avalable în versiunea ATEX (opțional)
[II 1GD Ex ia IIC T4 ... T6 Ga]
[II 1GD Ex ia IIIC T135ºC Da]
date tehnice
Clasa de precizie C3-C4
Putere nominală 2 ± 0,1% mV / V
Vmin Emax / 15000
Excitație tensiune 5 ÷ 15V
Intrare Rezistență 350 ± 3Ω
Ieșire Rezistență 350 ± 3Ω
-10ºC Temperatura de compensare / + 40 ° C
Limitele temperaturii -30 ° C / + 70 ° C
Rezistența de izolație> 5000 MQ

Caracteristici tehnice

Caracteristică	Detalii
Accuracy class	C3-C4
Rated output	2 ± 0.1% mV/V
Vmin	Emax/15000
Excitation Voltage	5÷15V
Input Resistance	350 ± 3Ω
Output Resistance	350 ± 3Ω
Temperature Compensation	-10ºC/+40ºC
Temperature limits	-30ºC/ +70ºC
Insulation resistance	> 5000 MΩ