DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Indicator cantarire SC4



Indicator cantarire SC4. Producator: Sensocar.

Descriere

WEIGH-TARE 10000 Divisions

Class III Maximum Certification 10000 divisions 1µV step 40Ω load (16 load cells of 700Ω

Additional plug & work hardware

Optimized software with all program optionals embedded 19, 40, 60 and 100 mm versions, with ultrabright LED.

Manual weight adjustment

Autocalibration without needing new adjustments.

Weighing accumulation and autoaccumulation.

On/Off by key.

Manual tare function.

Piececounter function.

Dynamic and animal weighing dedicated functions.

Discharge function for GROSS-TARE-NET tickets.

Flexible and fully-programmable multirange

User-definible linearization until 16 points.

Ticket repetition and ticket-per-weighing option.

Data dumping and configuration through PC.

6 selectable languages: Spanish, Portuguese, French, Italian, English and German.

Versions:

- SC4/A: Visor analógico / Analogic Indicator
- SC4/D: Digital load cells indicator
- SC4/BAT12: Battery

Both versions can include an external 12 V battery

INOX shell 6 digits 19 mm

For desktop or wall hanging use

Basic configuration

· Weight-Tare	
· Pieces Counter	
· Weight accumulations	

· Multirange	
· Communications RS-232 port communication	
· Compatible protocols	
· Languages	Spanish, English, French, Italian & Portuguese

Software

- Span, fraction and decimals fully customizables.
- Extended accumulation as standard, millions of accumulations with 48-bit totalizer.
- Accumulated Big Total option.
- Scroll, ticket’s header and foot customizables.
- Communication channels Self-testing as standard.
- Negative auto-zero as standard to avoid

Optional hardware

- IP-65 protection class against humidity.
- Internal 6V battery.
- External 12V battery.
- Clock, calendar and additional memory.
- 2 Optocoupled inputs and 6 relay outputs
- Current output for automata.
- Voltage output for automata.
- Second optocoupled serial channel for printer
- Converts 1st or 2nd RS232 optocoupled channel to RS485.
- Converts 1st or 2nd RS232 channel to RF
- Bibascule
- DSD feature (until 4000 weighings)

Available printers

· DPU 414 from SEIKO
· LX-300 from EPSON
· SRP 270 from SAMSUNG
· SP298 from STAR
· TM295 from EPSON

Labelers

· T402 from ZEBRA
· EZ4TT from C.ITOH

Technical data

Accuracy class	III
Maximum number of verification scale intervals	-10000
Load cell excitation power supply	8 V DC
Max. signal voltage for dead load	16 mV
Minimum signal voltage for dead load	0 mV
Minimum input voltage per verification scale interval	1 µV
Measuring range minimum voltage	8 mV

Measuring range maximum voltage	24 mV
Minimum load cell impedance	40 Ω
Maximum load cell impedance	2000 Ω
Minimum temperature range	-10º C
Maximum temperature range	40º C
Power supply requirements (options SC1/A or SC1/D)	220 V AC
Power supply requirements (SC1/BAT12)	12 V DC
Sense system	Available
Load cell cable length	
4 wire systems	5 m/mm2
6 wire systems	No limit

Cântărirea-TARE 10000 Divizii

Clasa III de certificare maximă 10000 divizii 1µV pas

Sarcină 40Ω (16 celule de sarcină de 700Ω

Plug & hardware suplimentar de lucru

Software-ul optimizat cu toate opționale programului încorporate 19, 40, 60 și 100 de versiuni mm, cu Ultrabright LED.

Reglare manuală greutate

Autocalibrare fără a avea nevoie de noi ajustări.

Cântărire acumulare și autoaccumulation.

ON / OFF cu tasta.

Funcția manual tare.

Funcția Piececounter.

Dinamic și animale de cântărire funcții dedicate.

Funcția de descărcare de gestiune pentru bilete GROSS-TARE-NET.

Multirange flexibil și complet programabile

-Utilizator definible liniarizare până la 16 de puncte.

Repetiție bilet și opțiunea bilet pe-cântărire.

Date de dumping și de configurare prin intermediul PC-ului.

6 limbi selectabile: spaniolă, portugheză, franceză, italiană, engleză și germană.

Versiuni:

- SC4 / A: Visor analógico / Analogic Indicator
- SC4 / D: Indicator celule de sarcină digitală
- SC4 / BAT12: Baterie

Ambele versiuni pot include o baterie externă de 12 V

Coajă INOX 6 cifre 19 mm

Pentru desktop sau pe perete utilizare

Configurația de bază

- Greutate-Tare
- Piese Counter
- Acumulări Greutate
- Multirange
- Comunicatii RS-232 de comunicare portul
- Protocoale compatibile
- Spaniolă, engleză, franceză, italiană și portugheză

Software-ul

- Span, fracțiune și zecimale customizables complet.
- Acumulare Extended standard, milioane de acumulări cu 48 de biți totalizator.

- Acumulat opțiune Big total.
- Scroll, antet și picior customizables bilete de.
- Canalele de comunicare auto-testare standard.
- Negativ auto-zero ca standard, pentru a evita

Hardware opțional

- Clasa IP 65 de protecție împotriva umidității.
- 6V internă a bateriei.
- 12V Externe acumulator.
- Ceas, calendar și memorie suplimentară.
- 2 intrări Optocoupled și 6 ieșiri de releu
- Ieșire de curent pentru automate.
- Ieșire de tensiune pentru automate.
- Optocoupled al doilea canal serial pentru imprimantă
- Convertește 1 sau 2 RS232 optocoupled canal la RS485.
- Convertește 1 sau 2 canale RS232 la RF
- Bibascule
- Caracteristica DSD (până 4000 cântăriri)

Imprimante disponibile

- DPU 414 de SEIKO
- LX-300 de la Epson
- SRP 270 de la Samsung
- SP298 de la STAR
- TM295 de la Epson

Etichetatoare

- T402 de la ZEBRA
- EZ4TT din C.ITOH

date tehnice

Clasa de precizie III

Numărul maxim de verificare a scalei intervale -10000

Încărcați excitație celule de alimentare cu energie 8 V DC

Max. tensiune de semnal pentru sarcină mort 16 mV

Tensiune minimă de semnal pentru sarcină mort 0 mV

Tensiune minimă de intrare pe Interval de verificare 1 µV

Interval de măsurare de tensiune minimă 8 mV

Interval de măsurare de tensiune maximă de 24 mV

Impedanta de celule de sarcină minim 40 Ω

Impedanta de celule de sarcină maximă 2000 Ω

Interval minim de temperatură -10º C

Gama de temperatura maximă 40 ° C

Cerințe de alimentare (opțiuni SC1 / A sau SC1 / D) 220 V AC

Cerințe de alimentare (SC1 / BAT12) 12 V DC

Sistemul Sense Disponibil

Lungime cablu de încărcare de celule 4 sisteme de sârmă 5 m / mm2 6 sisteme de sârmă No Limit